




Positive Lock | Mark II, Positive Lock 250

TE Internal #: 1969865-1

Crimp Terminal Housings, Receptacle, Receptacle, 3 Position,
Straight, UL 94V-0, Black, Nylon, Carton, -40 - 130 °C [-40 - 266 °F],
Positive Lock 250

[View on TE.com >](#)

Terminals & Splices > Terminal Housings, Insulation Sleeves & Blocks > Crimp Terminal Housings



Terminal Type: **Receptacle**
Connector & Housing Type: **Receptacle**
Number of Positions: **3**
Terminal Orientation: **Straight**
UL Flammability Rating: **UL 94V-0**

Features

Product Type Features

Sealable	No
Connector & Housing Type	Receptacle

Configuration Features

Number of Positions	3
---------------------	---

Body Features

Primary Product Color	Black
-----------------------	-------

Contact Features

Terminal Type	Receptacle
Terminal Orientation	Straight
Contact Mating Retention	Without

Mechanical Attachment

Mating Alignment	Without
------------------	---------

Housing Features

--	--



Housing Material	Nylon
------------------	-------

Usage Conditions

Operating Temperature Range	-40 - 130 °C[-40 - 266 °F]
-----------------------------	----------------------------

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Method	Carton
------------------	--------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 63239-1
POSITIVE LOCK 250 REC 12-10 AWG
TPBR

TE Part # 170329-1
250 PL MKII REC. 15-10AWG PTBR

TE Part # 170327-1
250 PL MKII REC. 22-18AWG PTBR

TE Part # 170328-1
250 PL MKII REC. 18-14AWG PTBR

TE Part # 2238155-1
POS LOCK 250 Rec, MKII, 18-14 TPBR

TE Part # 2238156-1
POS LOCK 250 Rec, MKII, 22-18 TPBR

Also in the Series | Mark II

Automotive Connector Locks & Position Assurance(1)

Automotive Housings(21)

Automotive Terminals(18)

Connector Seals & Cavity Plugs(1)

Crimp Terminal Housings(76)

Insertion & Extraction Tools(2)

Other Automotive Connector Accessories(4)

Quick Disconnects(57)

Also in the Series | Positive Lock 250



Automotive Terminals(1)



Crimp Terminal Housings(192)



Insertion & Extraction Tools(3)



Insulation Boots & Sleeves(4)



Quick Disconnects(186)

Customers Also Bought



TE Part # 2151582-1
OCEAN_2.0_Applicator-S-110F165O-RSM




TE Part # 215882-6
AMP-LATCH MIL TYPE RCPT CONNECTOR




TE Part # 2836077-1
OCEAN_2.0_Applicator-S-070F100O-RSM



TE Part # 7-2150373-7
OCEAN-055F080F-CRIMPTOOLINGKIT



TE Part # 7-2266813-7
OCEAN_2.0_SPARE_PART_KIT-055F062F



TE Part # 7-2837932-7
OCEAN_2.0_SPARE_PART_KIT-062F091O



TE Part # 926298-5
UN-MNL STECK-GEH 4P



TE Part # 886281-000
FLHTC0311-26-2

Documents

Product Drawings

3P, 250 SERIES, POSITIVE LOCK MARK II

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1969865-1_A.2d_dxf.zip



English

Customer View Model

[ENG_CVM_CVM_1969865-1_A.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1969865-1_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[K-Style Infinite Switch Housings Flyer](#)

English

Product Specifications

[Product Specification](#)

English

Agency Approvals

[UL Report](#)

English