



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.5 - 1 mm²**

Mating Tab Width: **2.8 mm [.11 in]**

Mating Tab Thickness: **.51 mm [.02 in]**

Features

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]
Mating Tab Thickness	.51 mm[.02 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

--



Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Terminal Material Thickness	.25 mm[.01 in]
Product Length	14 mm, 14.9 mm[.551 in]
Compatible Insulation Diameter Range	2.03 - 3 mm[.08 - .118 in]
Wire Size	.5 - 1 mm ²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 - 110 °C[-40 - 230 °F]

Industry Standards

Compatible With Agency/Standards Products	CSA, UL
---	---------

Packaging Features

Packaging Quantity	500
Packaging Method	Loose Piece/Carton

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part



numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 61045-2
FASTON .187 SERIES (4.8 MM) TPBR

TE Part # 160668-2
110 FASTIN FASTON,REC.,20-16 AWG, PTBR

TE Part # 180441-2
110 FASTON,REC.,20-16 AWG,TPBR

TE Part # 151791-2
FASTON 375 REC FLAG 12-10 AWG TPBR LP

TE Part # 169048-1
DAHT ASSY

Also in the Series | FASTON 110

Crimp Terminal Housings(13)

Insertion & Extraction Tools(1)

PCB Terminals(22)

Quick Disconnects(169)


Customers Also Bought

TE Part # 6609070-3
16FCD10 D0=F7741

TE Part # T4110002051-000
M12,FEMALE,STRAIGHT,A CODE,5P, PG9,GOLD

TE Part # T4012008041-000
M8,SCREW, FEMALE,R/A,UNSHIELD, 4P,GOLD

TE Part # 4159206001
DSPL-NR1-X-50MM



TE Part # 963213-1
Dichtung F 962352



TE Part # 1-480698-0
02P UMNL PLUG HSG NATL



TE Part # 1676391-2
RN 0805 5K9 0.1% 10PPM 1KRL



TE Part # 1-967601-1
MESSERLEISTE3,0 10P



TE Part # ZPF000000000019427
FDBA 56-16-8 SN-K

Documents

Product Drawings

110 FASTON,REC.,20-17 AWG,TPBR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_160625-2_F.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_160625-2_F.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_160625-2_F.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Product Specification

English

Agency Approvals

UL Report

English