



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: **Housing**
Connector & Housing Type: **Plug**
Connector System: **Wire-to-Panel, Wire-to-Wire**
Number of Positions: **4**
Centerline (Pitch): **4.2 mm [.165 in]**

Features

Product Type Features

Rectangular Power Connector Type	Housing
Connector & Housing Type	Plug
Connector System	Wire-to-Panel, Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	4
Number of Rows	2

Electrical Characteristics

Operating Voltage	600 VAC
-------------------	---------

Contact Features

Contact Retention Within Housing	Without
Contact Type	Pin



Termination Features

Termination Method to Wire & Cable	Crimp
------------------------------------	-------

Mechanical Attachment

Connector Mounting Type	Panel Mount
-------------------------	-------------

Housing Features

Centerline (Pitch)	4.2 mm[.165 in]
Housing Color	Natural
Housing Material	Nylon 6/6

Dimensions

Connector Height	9.6 mm[.378 in]
Product Width	23.9 mm[.94 in]
Product Length	9.6 mm[.378 in]
Row-to-Row Spacing	4.2 mm[.165 in]

Usage Conditions

Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Industry Standards

CSA Rating	208567
UL Rating	Recognized
Compatible With Agency/Standards Products	CSA, UL
Compatible With Approved Standards Products	UL E28476
UL Flammability Rating	UL 94V-2
Glow Wire Rating	Standard Part - Not Glow Wire

Packaging Features

Packaging Quantity	500
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Yet Reviewed







China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts


 TE Part # 794954-4 4P RCPT VAL-U-LOK V2	 TE Part # 1586037-4 4P VERT HDR VAL-U-LOK V2	 TE Part # 1586041-4 4P VAL-U-LOK R/A HDR V2	 TE Part # 1586586-4 4P VAL-U-LOK BMI VRT HDR V2
 TE Part # 1969597-4 4P RCPT VAL-U-LOK V2	 TE Part # 1586043-4 4P VAL-U-LOK R/A HDR SCR MT V2	 TE Part # 1586075-4 4P RCPT VAL-U-LOK V2 BLK	 TE Part # 2415884-4 4P VERT HDR VAL-U-LOK V2

Customers Also Bought





TE Part # 2238017-1
VAL-U-LOK SKT BR SN 18-22AWG



TE Part # 1586316-1
VAL-U-LOK PIN BR SN 26-22 LP



TE Part # 66101-1
III+ SKT,18-16,30AU>10,LP




TE Part # 794407-4
MINI UNML SCKT 20-16 AWG SN




TE Part # 2267395-1
CPC CABLE CLAMP KIT, STD, SIZE 23, UV



TE Part # 1969612-2
2P FH PLUG VAL-U-LOK V0



TE Part # 2029180-4
4P PLUG SR VAL-U-LOK FH GW



TE Part # 2029180-5
5P PLUG SR VAL-U-LOK FH GW



TE Part # 2238020-1
VAL-U-LOK PIN BR TN 22-18 LP

Documents

Product Drawings
4P PM PLUG VAL-U-LOK V2

English

CAD Files
3D PDF

3D

Customer View Model
ENG_CVM_CVM_1969599-4_A_c-1969599-4-a.2d_dxf.zip

English

Customer View Model
ENG_CVM_CVM_1969599-4_A_c-1969599-4-a.3d_igs.zip

English

Customer View Model
ENG_CVM_CVM_1969599-4_A_c-1969599-4-a.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages



1-1773730-3 VAL-U-LOK Connectors with TPA Flyer

English

Product Specifications

Application Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English

Agency Approvals

UL Report

English