




Terminals & Splices > Terminal Housings, Insulation Sleeves & Blocks > Crimp Terminal Housings



Terminal Type: **Receptacle**
Connector & Housing Type: **Receptacle**
Number of Positions: **2**
Terminal Orientation: **Flag**
UL Flammability Rating: **UL 94V-2**

Features

Product Type Features

Sealable	No
Connector & Housing Type	Receptacle

Configuration Features

Number of Positions	2
---------------------	---

Body Features

Primary Product Color	Natural
-----------------------	---------

Contact Features

Terminal Type	Receptacle
Terminal Orientation	Flag
Contact Mating Retention	Without

Mechanical Attachment

Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)



Housing Features

Housing Material	Nylon
Centerline (Pitch)	5.58 mm[.22 in]

Dimensions

Product Length	19.05 mm[.75 in]
----------------	------------------

Usage Conditions

Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
-----------------------------	----------------------------

Industry Standards

UL Flammability Rating	UL 94V-2
------------------------	----------

Packaging Features

Packaging Method	Carton
------------------	--------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>




Compatible Parts

 TE Part # 63445-1 250 FASTON FLAG REC 18-12 AWG BR	 TE Part # 63445-2 250 FASTON FLAG REC 18-12 AWG TPBR	 TE Part # 2238171-3 250 FASTON,FLAG,REC.,22-12 AWG, TPBR	 TE Part # 1969422-2 250 FASTON HSG.,FLAG,REC.,2 POS, NATRUAL
---	--	---	---

Also in the Series | FASTON 250

 Compression Connectors(4)	 Crimp Terminal Housings(133)	 Insertion & Extraction Tools(6)	 Magnet Wire Terminals(1)
 PCB Terminals(134)	 Quick Disconnects(441)	 Splices(4)	

Customers Also Bought

 TE Part # 640905-1 PIDG FASTON Receptacle Quick Disconnects	 TE Part # 2-520181-2 ULTRA-FAST 187 ASY REC 22-18 AWG TPBR	 TE Part # 61118-1 MNL PIN 20-14 TPBR	 TE Part # 63010-2 250 FASTON FLAG REC 18-14 AWG TPBR
--	--	---	---






TE Part # 1060-16-0622
DEUTSCH Size 16 Crimp Contacts



TE Part # C21881-000
B-155-9004



TE Part # E74832-000
B-155-9003



TE Part # DT06-6S-KIT
DT06-6S AND WEG ONLY

Documents

Product Drawings

250 FASTON HSG. FLAG REC 5.6MM2P NATURAL

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_521663-1_L_c-521663-1-l.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_521663-1_L_c-521663-1-l.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_521663-1_L_c-521663-1-l.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Agency Approvals

UL Report

English