

Z-PACK | Z-PACK 2mm HM

TE Internal #: 646484-5

PCB Mount Shroud, Gray, Glass Filled Polyester, 150 Position, Z-

PACK 2mm HM

View on TE.com >





Connectors > Connector Accessories > Connector Caps & Covers











Connector Cover Type: PCB Mount Shroud

Primary Product Color: Gray

Primary Product Material: Glass Filled Polyester

Number of Positions: 150

Operating Temperature (Max): 125 °C [257 °F]

Features

Product Type Features

Connector Cover Type	PCB Mount Shroud
Configuration Features	
Number of Rows	5
Number of Positions	150
Body Features	
Primary Product Color	Gray
Primary Product Material	Glass Filled Polyester
Mechanical Attachment	
Mating Alignment Type	Polarization
Mating Alignment	With
Housing Features	
Centerline (Pitch)	2 mm[.079 in]
Dimensions	

15.4 mm[.055 in]

Product Width



Product Length	43.9 mm[1.728 in]
Product Height	14.9 mm[.586 in]
Row-to-Row Spacing	2 mm[.079 in]
Usage Conditions	
Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 - 125 °C[-67 - 257 °F]
Operation/Application	
Assembly Process Feature	Board Standoff
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Method	Tray

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



Compatible Parts





Also in the Series | Z-PACK 2mm HM








Backplane Power Connectors(6)



Connector Caps & Covers(62)





Connector Hardware(97)




Hard Metric Backplane Connectors



High Speed Backplane Connectors(1)



Insertion & Extraction Tools(2)



Customers Also Bought
























Documents

Product Drawings

2MM H.M.,A/B-22 SHROUD 4.5MM

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_646484-5_F.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_646484-5_F.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_646484-5_F.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use

Product Specifications



Application Specification

English