



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: **Housing**
Connector & Housing Type: **Plug**
Connector System: **Wire-to-Panel, Wire-to-Wire**
Number of Positions: **22**
Centerline (Pitch): **3 mm [.118 in]**

Features

Product Type Features

Rectangular Power Connector Type	Housing
Connector & Housing Type	Plug
Connector System	Wire-to-Panel, Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	22
Number of Rows	2

Electrical Characteristics

Operating Voltage	250 VDC
-------------------	---------

Contact Features

Contact Retention Within Housing	Without
Contact Type	Pin



Termination Features

Termination Method to Wire & Cable	Crimp
------------------------------------	-------

Mechanical Attachment

Strain Relief	Without
Mating Alignment Type	Polarization
Mating Retention	With
Mating Alignment	With
Panel Mount Feature	With
Panel Mount Feature Type	Locking Latch
Mating Retention Type	Locking Tab
Connector Mounting Type	Panel Mount

Housing Features

Centerline (Pitch)	3 mm [.118 in]
Housing Color	Black
Housing Material	Nylon

Dimensions

Panel Thickness (Recommended)	1.57 - 2.3 mm [.062 - .091 in]
Compatible Insulation Diameter (Max)	1.52 mm [.06 in]
Connector Height	8.71 mm
Product Length	33.85 mm
Row-to-Row Spacing	3 mm [.118 in]

Usage Conditions

Operating Temperature Range	-40 - 105 °C [-40 - 221 °F]
-----------------------------	-----------------------------

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Industry Standards

UL Flammability Rating	UL 94V-0
Glow Wire Rating	Standard Part - Not Glow Wire

Packaging Features

Packaging Quantity	250
Packaging Method	Bag



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



Also in the Series | Micro MATE-N-LOK



[Connector Contacts\(27\)](#)



[Insertion & Extraction Tools\(1\)](#)



[Rectangular Power Connectors\(469\)](#)

Customers Also Bought



TE Part # 1-794610-1
[MICRO MNL RPT CNT,LS PC 15AU L](#)



TE Part # 1-794617-6
[16POS,MICRO MNL,RCPT HSG](#)



TE Part # 794617-8
[8POS,MICRO MNL,RCPT HSG](#)



TE Part # 794615-6
[PANEL MT DBL ROW HSG 6 POS](#)



TE Part # 1-794611-1
[MICRO MNL RPT CNT,LS PC,15AU,L](#)



TE Part # 1-794612-1
[PIN CONT 20-24 15 GOLD L/P](#)



TE Part # 592387J001
[V2-4.0-0-SP-SM](#)



TE Part # 1-794615-6
[PANEL MT DBL ROW HSG 16 POS](#)



TE Part # 2-794616-4
[FREE HANG DBL ROW HSG 24 POS](#)



TE Part # 2-1617002-3
[B07A932BC1-0281 = RELAY.](#)

Documents

Product Drawings

[PANEL MT DBL ROW HSG 22 POS](#)

English

CAD Files

[3D PDF](#)

3D

Customer View Model

[ENG_CVM_CVM_2-794615-2_C1.2d_dxf.zip](#)



English

Customer View Model

[ENG_CVM_CVM_2-794615-2_C1.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_2-794615-2_C1.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG](#)

English

MICRO MATE-N-LOK CONNECTOR SYSTEM

English

Product Specifications

[Application Specification](#)

English