



Terminals & Splices > Terminal Housings, Insulation Sleeves & Blocks > Crimp Terminal Housings



Terminal Type: **Receptacle**
Connector & Housing Type: **Receptacle**
Number of Positions: **2**
Terminal Orientation: **Straight**
Primary Product Color: **Natural**

Features

Product Type Features

Sealable	No
Connector & Contact Terminates To	Wire & Cable
Connector & Housing Type	Receptacle

Configuration Features

Number of Positions	2
---------------------	---

Body Features

Primary Product Color	Natural
-----------------------	---------

Contact Features

Terminal Type	Receptacle
Terminal Orientation	Straight
Contact Mating Retention	With

Mechanical Attachment

Mating Retention Type	Latch
-----------------------	-------



Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	Nylon
Centerline (Pitch)	6 mm[.236 in]

Dimensions

Product Length	25 mm[.984 in]
----------------	----------------

Usage Conditions

Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
-----------------------------	----------------------------

Packaging Features

Packaging Quantity	100
--------------------	-----

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>







Compatible Parts

 TE Part # 170258-2 FF 250 REC 14-12AWG TPBR REREELING	 TE Part # 170258-1 FF 250 REC 14-12AWG BR REREELING	 TE Part # 1-626040-0 RELY BASE MOLDING 5W POLYPROPYLENE	 TE Part # 880192-2 5 WAY FF 110 HSG REC NYLON 66 NATURAL
 TE Part # 176986-1 FF 250 PLUG HSG 1P NYLON NAT	 TE Part # 968864-1 FF 110 REC HSG 2P NYLON NAT	 TE Part # 178024-7 FF 250 CAP HSG DBL 6P PLATE	 TE Part # 2302009-1 W/H REAR BLOWER, AI-TATA X104


Also in the Series | FASTIN-FASTON 250

 Crimp Terminal Housings(211)	 Insertion & Extraction Tools(2)	 PCB Terminals(2)	 Quick Disconnects(254)
---	---	---	---

Customers Also Bought

 TE Part #171897-1 FF 250 REC HSG 6P NYLON NAT	 TE Part #172133-1 FF 250 CAP HSG 4P NYLON NAT	 TE Part #171898-1 FF 250 PLUG HSG 6P NYLON NAT	 TE Part #170342-1 250 FASTON,REC.,20-14 AWG,BR
--	---	---	---






TE Part #172127-1
FF 250 PLUG HSG 1P NYLON NAT



TE Part #170342-2
250 FASTON,REC.,20-14 AWG,TPBR



TE Part #170032-2
250 FASTON,REC.,20-14 AWG,BR



TE Part #T1519101000-000
H10A-ADMS



TE Part #176986-1
FF 250 PLUG HSG 1P NYLON NAT

TE Part #K1142300
Limit switch G12-341-A-025 911

Documents

Product Drawings

FF 250 REC HSG 2P NYLON NAT

English

CAD Files

Customer View Model

ENG_CVM_CVM_172130-1_D.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_172130-1_D.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_172130-1_D.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

White Paper: Nylon Discoloration

English

Product Specifications

Application Specification

English

Instruction Sheets

Customer Manual (non U.S.)



Japanese

"250" Series, Housing Lance Connector

Japanese

Agency Approvals

UL Report

English