

PLASTI-GRIP


TE Internal #: 1377173-1

Closed Ring Tongue Terminal, 22 - 16 AWG, M8 / 5/16 Stud Size,
7.92 mm [.312 in] Stud Diameter, Closed Barrel, Straight, Tin,
PLASTI-GRIP

[View on TE.com >](#)



Terminals & Splices > Ring Terminals



Ring Terminal Product Type: Closed Ring Tongue Terminal

Wire Size: 509 - 3260 CMA

Stud Size: 5/16, M8

Features

Product Type Features

Ring Terminal Product Type	Closed Ring Tongue Terminal
Stud Size	5/16, M8
Sealable	No

Wire Insulation Support Retention Type	Insulation Support
--	--------------------

Body Features

Product Weight	.928 g[.0327 oz]
----------------	------------------

Contact Features

Barrel Type	Closed
Terminal Orientation	Straight
Terminal Plating Material	Tin

Mechanical Attachment

Wire Insulation Support	With
-------------------------	------

Dimensions

Wire Size	509 - 3260 CMA
Stud Diameter	7.92 mm[.312 in]



Tongue Thickness	.79 mm[.031 in]
Product Length	27.69 mm[1.09 in]
Compatible Insulation Diameter (Max)	3.56 mm[.14 in]
Compatible Insulation Diameter Range	2.67 - 3.56 mm[.105 - .14 in]

Usage Conditions

Insulation Option	Partially Insulated
Operating Temperature Range	90 °C[194 °F]

Operation/Application

Compatible With Wire Base Material	Copper
Compatible With Wire Plating Material	Tin

Industry Standards

Government Qualified Terminal	No
-------------------------------	----

Packaging Features

Packaging Quantity	100
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous



materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 34151
PG R 22-16 COMM 22-18 MIL 5/16

TE Part # 1SET121007R0000
RT015-080-V

Also in the Series | PLASTI-GRIP

Compression Connectors(3)

Crimp Wire Pins, Tabs & Ferrules(22)

Ring Terminals(324)

Spade Terminals(178)

Splices(47)

Customers Also Bought


TE Part # 3-520339-2
ULTRA-FAST 187 ASY REC 16-14 AWG
TPBR

TE Part # 1-966067-2
FER,WIRE,PL SLV,1.50/16,L8,BLACK,LP


TE Part # 2-520411-2
ULTRA-FAST 187 ASY REC 22-18 TPBR

TE Part # 34150
PG R 22-16 COMM 22-18 MIL 1/4





TE Part # 794954-2
2P RCPT VAL-U-LOK V2



TE Part # 1586315-1
VAL-U-LOK SKT BR SN 24-18 LP



TE Part # 2102352-4
CeeLok FAS-T, Receptacle kit, ZnNi, A



TE Part # 2102353-4
CeeLok FAS-T, Plug Kit, ZnNi, A



TE Part # 2151500-2
OCEAN_2.0_APPLICATOR-S-090F130F-RSA



TE Part # CONMCX002
MCX Jack 50 Ohm PCB Through Hole

Documents

Product Drawings

SMP 0-0034151-0

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1377173-1_H1.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1377173-1_H1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1377173-1_H1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

RADIATION_RESISTANT_PRE-INSULATED_TERMINALS_SPLICES

English

Product Specifications

Application Specification

English