



Part Number : 1731120328

Series Number : 173112  
Product Category : D-Sub Contacts

Product Description : FCT High Power Contact,  
Male, Straight, Crimp, 0.20µm Gold Mating  
Plating, 3.00-5.00µm Nickel Termination  
Plating, 10.0A, 16-20 AWG  
Status : Active  
Engineering Number : FMP002P190


Documents & Resources

Drawings  
Drawing 1731120328\_sd.pdf

Specifications  
Application Specification 2195600660-000.pdf  
Packaging Specification 1731120008-PK-000.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Contains Lead per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant with Exemption 6(c) per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## Part Details

### General

Status	Active
Category	D-Sub Contacts
Series	173112
Description	FCT High Power Contact, Male, Straight, Crimp, 0.20µm Gold Mating Plating, 3.00-5.00µm Nickel Termination Plating, 10.0A, 16-20 AWG
Contact Type	High Power
Product Family	FCT D-Sub Connectors
Product Name	FCT Products
Type	Mixed Layout
UPC	191128055635

### Electrical

Current - Maximum per Contact	10.0A
-------------------------------	-------

### Physical

Durability (mating cycles max)	200
Gender	Male
Material - Contact	Copper Alloy
Material - Plating Mating	Gold over Nickel
Material - Plating Termination	Nickel over Copper
Material - Retaining Clip	Copper Alloy
Net Weight	2.000/g
Orientation	Straight
Packaging Type	Bag
Plating min - Mating	0.200µm
Plating min - Termination	3.000-5.000µm
Temperature Range - Operating	-55° to +155°C
Termination Style	Crimp
Wire Size (AWG)	16, 18, 20

---

Use with Part(s)

Description	Part Number
Use With	FCT Mixed Layout Connectors

---

Application Tooling

Global

Description	Part Number
FCT Hand Crimp Tool, 8-Step Adjust	<u>1731121731</u>
FCT Locator for High Power Contacts	<u>1731121734</u>
FCT Removal Tool for Size 8 Contacts	<u>1731121747</u>