



VAL-U-LOK

TE Internal #: 1969613-6

Rectangular Power Connectors, Housing, Plug, Wire-to-Wire / Wire-to-Panel, 6 Position, 4.2 mm [.165 in] Centerline, Wire & Cable, UL 94V-0

[View on TE.com >](#)

Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: **Housing**  
Connector & Housing Type: **Plug**  
Connector System: **Wire-to-Panel, Wire-to-Wire**  
Number of Positions: **6**  
Centerline (Pitch): **4.2 mm [ .165 in ]**

Features

Product Type Features

|                                   |                             |
|-----------------------------------|-----------------------------|
| Rectangular Power Connector Type  | Housing                     |
| Connector & Housing Type          | Plug                        |
| Connector System                  | Wire-to-Panel, Wire-to-Wire |
| Sealable                          | No                          |
| Connector & Contact Terminates To | Wire & Cable                |

Configuration Features

|                     |   |
|---------------------|---|
| Number of Positions | 6 |
| Number of Rows      | 2 |

Electrical Characteristics

|                   |         |
|-------------------|---------|
| Operating Voltage | 600 VAC |
|-------------------|---------|

Contact Features

|                                  |         |
|----------------------------------|---------|
| Contact Retention Within Housing | Without |
| Contact Type                     | Pin     |



Termination Features

|                                    |       |
|------------------------------------|-------|
| Termination Method to Wire & Cable | Crimp |
|------------------------------------|-------|

Mechanical Attachment

|                         |             |
|-------------------------|-------------|
| Connector Mounting Type | Panel Mount |
|-------------------------|-------------|

Housing Features

|                    |                 |
|--------------------|-----------------|
| Centerline (Pitch) | 4.2 mm[.165 in] |
| Housing Color      | Natural         |
| Housing Material   | Nylon 6/6       |

Dimensions

|                    |                  |
|--------------------|------------------|
| Connector Height   | 11.6 mm[.457 in] |
| Product Width      | 23.8 mm[.906 in] |
| Product Length     | 13.8 mm[.543 in] |
| Row-to-Row Spacing | 4.2 mm[.165 in]  |

Usage Conditions

|                             |                            |
|-----------------------------|----------------------------|
| Operating Temperature Range | -40 - 105 °C[-40 - 221 °F] |
|-----------------------------|----------------------------|

Operation/Application

|                     |                |
|---------------------|----------------|
| Circuit Application | Power & Signal |
|---------------------|----------------|

Industry Standards

|                                             |                               |
|---------------------------------------------|-------------------------------|
| CSA Rating                                  | 208567                        |
| UL Rating                                   | Recognized                    |
| Compatible With Agency/Standards Products   | CSA, UL                       |
| Compatible With Approved Standards Products | UL E28476                     |
| UL Flammability Rating                      | UL 94V-0                      |
| Glow Wire Rating                            | Standard Part - Not Glow Wire |

Packaging Features

|                    |     |
|--------------------|-----|
| Packaging Quantity | 500 |
| Packaging Method   | Bag |

Product Compliance

For compliance documentation, visit the product page on TE.com>

|                              |           |
|------------------------------|-----------|
| EU RoHS Directive 2011/65/EU | Compliant |
| EU ELV Directive 2000/53/EC  | Compliant |



|                                               |                                                                                                                               |
|-----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold                                                                                       |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JAN 2024 (240)<br>Candidate List Declared Against: JAN 2024 (240)<br>Does not contain REACH SVHC |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free                                           |
| Solder Process Capability                     | Not reviewed for solder process capability                                                                                    |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

|                                                    |                                                           |                                                     |                                                        |
|----------------------------------------------------|-----------------------------------------------------------|-----------------------------------------------------|--------------------------------------------------------|
| <br>TE Part # 1586038-6<br>6P VRT HDR VAL-U-LOK V0 | <br>TE Part # 1586019-6<br>6P RCPT VAL-U-LOK V0           | <br>TE Part # 1969614-6<br>6P RCPT VAL-U-LOK V0     | <br>TE Part # 1586040-6<br>6P VAL-U-LOK VRT HDR W/P V0 |
| <br>TE Part # 1586042-6<br>6P VAL-U-LOK R/A HDR V0 | <br>TE Part # 1586044-6<br>6P VAL-U-LOK R/A HDR SCR MT V0 | <br>TE Part # 2029029-6<br>6P RCPT VAL-U-LOK V0 BLK | <br>TE Part # 2029094-6<br>6P RCPT VAL-U-LOK V0 RED    |





TE Part # 2029100-6  
6P RCPT VAL-U-LOK V0 BLUE

Customers Also Bought



TE Part # 1971777-4  
PTL TPA HIGH TEMP 1 x 4 BLACK



TE Part # 1971786-1  
Tab Contact - POWER TRIPLE LOCK



TE Part # 1969442-6  
EP 2.5 TPA Housing, 6 Pos



TE Part # 1969443-3  
EP 2.5 TPA Retainer, 3 Pos



TE Part # 1-1969567-4  
HOUSING, PLUG, GWT, DUAL ROW, EP2.5



TE Part # 1969443-2  
EP 2.5 TPA Retainer, 2 Pos



TE Part # 1-2132782-2  
12 pos. EP II breakaway retain



TE Part # 1744544-5  
EP II TPA 05P, BLACK

Documents

Product Drawings

6P PM PLUG VAL-U-LOK V0

English

CAD Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_1969613-6\_A\_c-1969613-6-a.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_1969613-6\_A\_c-1969613-6-a.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_1969613-6\_A\_c-1969613-6-a.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.



Datasheets & Catalog Pages

1-1773730-3 VAL-U-LOK Connectors with TPA Flyer

English

Product Specifications

Application Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English

Agency Approvals

UL Report

English