AMP | Multilock Connector System


TE Internal #: 936242-1

Housing for Male Terminals, Wire-to-Wire, 8 Position, .157 in [4 mm] Centerline, Natural, Signal, Multilock Connector System

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > MULTILOCK, CONNECTOR HOUSING



Connector System: Wire-to-Wire

Number of Positions: 8

Connector & Housing Type: Housing for Male Terminals

Centerline (Pitch): 4 mm [.157 in]

Sealable: No

All MULTILOCK, CONNECTOR HOUSING (404)

Features

Product Type Features

Troduct Type reatures	
Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Wire
Connector & Housing Type	Housing for Male Terminals
Sealable	No
Primary Locking Feature	Integrated in Housing
Configuration Features	
Blank Cavity Position	0
Number of Positions	8
Number of Rows	2
Body Features	
Cable Exit Angle	180°
Primary Product Color	Natural
Contact Features	
Contact Size	2.3mm
Contact Type	Tab

2.3 mm[.09 in]

Mating Tab Width



Mechanical Attachment

Terminal Position Assurance	Yes
Strain Relief	Without
Mating Alignment Type	Polarized
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PBT
Centerline (Pitch)	4 mm[.157 in]

Dimensions

Connector Height	16.7 mm[.657 in]
Product Width	34 mm[1.33 in]
Product Length	25.2 mm[.992 in]
Row-to-Row Spacing	5 mm[.197 in]

Usage Conditions

Operating Temperature (Max)	70 °C, 75 °C, 80 °C[158 °F][167 °F][176 °F]
Operating Temperature Range	-40 - 80 °C[-40 - 176 °F]

Operation/Application

Circuit Application	Signal	
	5191131	

Industry Standards

UL Flammability Rating	UL 94HB	
------------------------	---------	--

Packaging Features

Packaging Quantity	260
Packaging Method	Bag

Other

Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant



China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts









Also in the Series | Multilock Connector System

Position Assurance(3)













Connector Seals & Cavity Plugs(2)



Insertion & Extraction Tools(6)



Other Automotive Connector Accessories(12)



PCB Headers & Receptacles(152)

Customers Also Bought







TE Part # 2295167-1 22POS,0.64 MALE GEN. Y,TABHSG, ASSY,SLD







Documents

Product Drawings
090III 8P CAP ASSY

English

CAD Files

Customer View Model

ENG_CVM_CVM_936242-1_B.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_936242-1_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_936242-1_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use.

Housing for Male Terminals, Wire-to-Wire, 8 Position, .157 in [4 mm] Centerline, Natural, Signal, Multilock Connector System



Datasheets & Catalog Pages

MULTILOCK Connector System

English

Product Specifications

Product Specification

English