



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Tab**

Wire Size: **1021 - 2048 CMA**

Mating Tab Width: **2.8 mm [.11 in]**

Features

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Tab
Mating Tab Width	2.8 mm[.11 in]
Mating Tab Thickness	.79 mm[.031 in]
Terminal Orientation	Straight
Contact Base Material	Copper Zinc Alloy
Terminal Plating Material	Silver
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Locking Lance Height	1.2 mm[.047 in]
----------------------	-----------------



Mating Retention Type

Locking Lance

Dimensions

Product Length	22.5 mm[.886 in]
Compatible Insulation Diameter Range	1.4 - 2.3 mm[.055 - .09 in]
Wire Size	1021 - 2048 CMA

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 - 140 °C[-40 - 284 °F]

Packaging Features

Packaging Quantity	1000
Packaging Method	Box

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>



Compatible Parts



TE Part # 1-1579007-4
EXTRACTION TOOL




TE Part # 4-1579007-3
EXTRACTION TOOL KIT




TE Part # 169400
CERTI-LOK FRAME W/O DIES


Also in the Series | FASTIN-FASTON 110




Automotive Housings(6)




Automotive Terminals(5)



Crimp Terminal Housings(34)



Insertion & Extraction Tools(3)



Quick Disconnects(83)

Customers Also Bought



TE Part # DRC13-24PB
HDR, 24P, BLK, RA, 1032 FLG, SN/NI /CU, B



TE Part # 1-776262-4
14POS,PIN DIA 1.3,HDR ASSY, 180DEG,COD 4



TE Part # 172331-1
MINI UNIVERSAL MATE-N-LOK CAP HOUSING 6P



TE Part # 41124
RING .190 (4.82 MM) 12-10 AWG TPBR



TE Part # 7-1393116-1
KUMP-11D18-12=KU

TE Part # 1879352-1
RR02 5% R33 AMMO

TE Part # 3-2316113-4
2MM,REC,CNT,CRIMP,24-28AWG,0.1UM,LP

TE Part # 394971-E
SRCA 1,27 3 F 1 IDC22 137 E1 094 1,27 TR

TE Part # 364241-E
SRCBUG A 2,54 2 6 CSI 163 E1 ADV TRAY J

Documents

Product Drawings

FF 110 (2.8 X 0.8 MM) TAB SSP CUZN30

English

FF 110 (2.8 X 0.8 MM) TAB SSP CUZN30

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_928931-1_P.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_928931-1_P.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_928931-1_P.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.