



Terminals & Splices > PCB Terminals



PCB Terminal Type: **Tab**
PCB Thickness (Recommended): **1.57 mm [.062 in]**
Mating Tab Width: **6.35 mm [.25 in]**
Mating Tab Thickness: **.8 mm [.031 in]**
PCB Hole Diameter: **1.4 mm [.055 in]**

Features

Configuration Features

Connection Capacity	Single
---------------------	--------

Contact Features

PCB Contact Termination Area Plating Material Thickness	3.81 μm[150 μin]
Contact Underplating Material Thickness	1.27 μm[50 μin]
Contact Mating Area Plating Material Thickness	3.81 μm[150 μin]
PCB Terminal Type	Tab
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.8 mm[.031 in]
Terminal Plating Material	Tin
Contact Underplating Material	Nickel
Terminal Size	6.35
Terminal Orientation	Right Angle

Termination Features

Termination Method to Printed Circuit Board	Through Hole - Solder
---	-----------------------



Product Terminates To	Printed Circuit Board
Mechanical Attachment	
Wire Insulation Support	Without
Dimensions	
Extension Below Board	3.81 mm[150 in]
Terminal Material Thickness	.8 mm[.031 in]
PCB Thickness (Recommended)	1.57 mm[.062 in]
PCB Hole Diameter	1.4 mm[.055 in]
Profile Height from PCB	7.62 mm[.304 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	-30 - 110 °C[-22 - 230 °F]
Industry Standards	
Compatible With Agency/Standards Products	CSA, UL
Packaging Features	
Packaging Quantity	8000
Packaging Method	Package
Product Compliance	
For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 63860-1 187 FASTON TAB TPBR	 TE Part # 63951-1 250 FASTON TAB TPBR	 TE Part # 1217061-1 187 FASTON,FLAG,TAB,TNBR	 TE Part # 63949-1 250 FASTON TAB TPBR
 TE Part # 1742303-1 250 FASTON,PCB TAB,TNBR	 TE Part # 63950-1 250 FASTON TAB TPBR	 TE Part # 63951-4 250 FASTON TAB TPBR	 TE Part # 1217062-1 187 FASTON,FLAG,PCB TAB,TNBR
 TE Part # 63860-2 187 FASTON TAB TPBR	 TE Part # 63951-8 250 FASTON TAB TPBR	 TE Part # 63824-5 250 FASTON TAB TPBR	 TE Part # 1217136-3 250 FASTON,PCB TAB,TNBR
 TE Part # 63950-6 FASTON 250 PCB TAB BR			



Also in the Series | FASTON 250

Compression Connectors(4)	Crimp Terminal Housings(133)	Insertion & Extraction Tools(6)	Magnet Wire Terminals(1)
PCB Terminals(134)	Quick Disconnects(441)	Splices(4)	

Customers Also Bought

TE Part # 207526-7 SKT HDR ASSY,9 POSN,METRIMATE	TE Part # 1618002-7 EV200AAANA=RELAY, EV200 SPST-N	TE Part # 1-338084-6 4/4 INV.MOD.JACK	TE Part # 640445-5 05P MTA156 HDR ASSY FL/STR SN
TE Part # 640445-8 08P MTA156 HDR ASSY FL/STR SN	TE Part # 1544210-2 CTS 2180 ETAME	TE Part # 240345J001 Versafit-V2 Heat Shrink Tubing	TE Part # 3-644617-5 05P MTA156 HDR ASY PO RA FB LF
TE Part # 6-2176421-4 TLRP 2512 2.0W R068 1% 50PPM 4K RL			



Documents

Product Drawings

250 FASTON TAB TPBR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_63952-1_K_c-63952-1-k.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_63952-1_K_c-63952-1-k.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_63952-1_K_c-63952-1-k.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

FASTON PCB Tabs and Receptacles

English

PRINTED CIRCUIT BOARD TERMINALS AND DISCONNECTS

English

Product Specifications

FASTON* 110, 187, 205, 250, and 312 Series Tab Contacts for Printed Circuit (PC) Board Applications

English

Agency Approvals

CSA Certificate

English

CSA Certificate

English