



Relays & Contactors > Relays > Signal Relays



Contact Voltage Rating: 125 VDC

Coil Power Rating DC: 66 mW

Isolation (HF Parameter): -18dB @ 900MHz, -30dB @ 100MHz

Insertion Loss (HF Parameter): -.12dB @ 100MHz, -1.9dB @ 900MHz

Features

Configuration Features

Insulation Special Features	2500V Initial Surge Withstand Voltage between Contacts & Coil
Contact Special Features	Bifurcated/Twin Contacts
Contact Arrangement	1 Form C (CO)
Contact Number of Poles	1

Electrical Characteristics

Insulation Initial Dielectric Between Open Contacts	500 Vrms
Contact Limiting Short-Time Current	1 A
Voltage Standing Wave Ration (HF Parameter)	1.06 @ 100MHz, 1.75 @ 900MHz
Power Consumption	65 - 130 mW
Contact Limiting Making Current	1 A
Contact Limiting Continuous Current	1 A
Insulation Initial Dielectric Between Contacts & Coil	1500 Vrms
Contact Limiting Breaking Current	1 A
Contact Switching Load (Min)	10mA @ .02V
Coil Resistance	137 Ω
Contact Voltage Rating	125 VDC
Coil Power Rating DC	66 mW
Coil Voltage Rating	3 VDC
Contact Current Rating	1 A
Contact Switching Voltage (Max)	125 VDC



Signal Characteristics

Isolation (HF Parameter)	-18dB @ 900MHz, -30dB @ 100MHz
Insertion Loss (HF Parameter)	-.12dB @ 100MHz, -1.9dB @ 900MHz

Body Features

Product Weight	2 g[.0705 oz]
----------------	---------------

Contact Features

Contact Plating Material	Gold-Rhodium
Contact Material	PdNi

Termination Features

Relay Connection Type	PCB Termination
Terminal Configuration	PCB Pins

Mechanical Attachment

Product Mount Type	Printed Circuit Board
--------------------	-----------------------

Dimensions

Insulation Clearance Between Contact & Coil	.75 mm[.03 in]
Insulation Creepage Between Contact & Coil	.75 mm[.03 in]
Product Width	7.6 mm[.299 in]
Product Length	13 mm[.511 in]
Product Height	6.9 mm[.271 in]

Usage Conditions

Environmental Ambient Temperature (Max)	85 °C[85 °F]
Operating Temperature Range	-40 - 85 °C

Operation/Application

Actuating System	DC
Solder Process	Wave Solder
Performance Type	High Sensitive
Coil Magnetic System	Monostable, Polarized

Packaging Features

Packaging Method	Box & Tube, Tube
------------------	------------------

Other

Length Class (Mechanical)	12 - 14 mm
---------------------------	------------



Insulation Creepage Class	0 - 1.5 mm
Height Class (Mechanical)	6 - 7 mm
Coil Power Rating Class	0 - 100 mW
Environmental Ambient Temperature Class	70 - 85 °C
Insulation Clearance Class	0 - 2.5 mm
Width Class (Mechanical)	6 - 8 mm
Contact Current Class	0 - 2 A

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



Customers Also Bought



Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-1393774-7_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-1393774-7_C.3d_igs.zip

English



Customer View Model
[ENG_CVM_CVM_1-1393774-7_C.3d_stp.zip](#)
English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications
[Product Specification](#)
English
Definitions General Purpose Relays
English