

TE Internal #: 12331-20
Pin Contact, Gold, 115 VAC, 115 VDC, Spring Contact Retention,
Size 20 Contact Size, Discrete Wire, 24 - 20 AWG Wire Size, .25 - .5
mm² Wire Size

[View on TE.com >](#)



Connectors > Contacts > Connector Contacts



Contact Type: **Pin**
Contact Mating Area Plating Material: **Gold**
Wire Contact Termination Area Plating Material: **Gold**
Operating Voltage: **115 VDC**

Features

Product Type Features

Sealable	Yes
----------	-----

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
-----------------------------------	---------------

Electrical Characteristics

Operating Voltage	115 VDC
-------------------	---------

Contact Features

Barrel Type	Closed
Contact Type	Pin
Contact Mating Area Plating Material	Gold
Wire Contact Termination Area Plating Material	Gold
Contact Retention Within Housing	With
Contact Size	Size 20
Contact Base Material	Copper Alloy
Contact Current Rating (Max)	7.5 A

Termination Features

Termination Method to Wire & Cable	Crimp
Product Terminates To	Wire & Cable

Mechanical Attachment



Contact Retention Type Within Housing	Spring
---------------------------------------	--------

Dimensions

Wire Size	.25 - .5 mm ²
-----------	--------------------------

Usage Conditions

Operating Temperature Range	-65 - 175 °C[-85 - 347 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power, Signal & High Speed Data
---------------------	---------------------------------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2023 (233) SVHC > Threshold: Pb (.7% in LEADED COPPER ALLOY) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 12333-20
CONT SOC ASSY

Customers Also Bought



TE Part # 106021-000
TXR54AB00-1408AI



TE Part # 12333-22
CONT SOC ASSY




TE Part # 12333-12
CONT SOC ASSY




TE Part # 131854-000
HT-SCE-1K-3/4-2.0-0



TE Part # 1532180-3
M83513/03-B03N, MCKS-N1-B-15P6G9-18.0




TE Part # EL6005-000
55PC0813-10-9CS2502



TE Part # 699874-000
CTA-0025



TE Part # 451893-000
SO63-3-9030CS2677



TE Part # Y88046-8-98SNV0030
PLUG ASSY



TE Part # ER6750-000
RW-200-1-1/2-0-SP-CS9376

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_12331-20_1.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_12331-20_1.3d_igs.zip

English

12331-20

Pin Contact, Gold, 115 VAC, 115 VDC, Spring Contact Retention, Size 20 Contact Size, Discrete Wire, 24 - 20 AWG Wire Size, .25 - .5 mm² Wire Size



Customer View Model

[ENG_CVM_CVM_12331-20_1.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.