




LA108-5/8X11-ZF

Ruland Adjustable Clamping Lever, Lever Length 108mm, Tapped Hole 5/8X11, Zinc Lever, Steel Inserts



Description

Ruland LA108-5/8X11-ZF is an adjustable clamping handle with a 108mm handle, 5/8X11 tapped hole, 23mm insert diameter, and 75mm overall height. The steel inserts combined with a zinc die-cast handle allow for use in heavy duty industrial applications. LA108-5/8X11-ZF has a textured finish on the handle making it easy for the user to grip in manufacturing environments with oil, coolant, or other lubricants. It is commonly found in packaging, printing, food processing, and manufacturing systems where conveyor rails, sensors, screens, and other components require frequent adjustments without the use of tools. The adjustable feature of this handle allows it to be used in confined spaces with limited hand access or where 360 degree rotation is not possible. Serrations connect the insert to the handle for easy disengagement. The user pulls the handle upwards by hand to disengage the serrations allowing it to be swiveled to the desired clamping position. Serrations automatically re-engage once the user releases the handle locking it in-place. A 5/8X11 tapped hole is designed to mate with an equivalently sized threaded stud or rod for a quick installation. LA108-5/8X11-ZF is black to seamlessly integrate with the aesthetics of most equipment. It is manufactured by Otto Ganter, stocked by Ruland, and RoHS3 and REACH compliant.

Product Specifications

Thread (TH)	5/8 in - 11 TPI	Lever Length L1	108 mm
Overall Height H1	75 mm	Hub Height H2	50.5 mm
Hub Diameter DH	30 mm	Handle Disengagement Travel H3	5 mm
Thread Depth T	22 mm	Sleeve Length L2	12 mm
Sleeve Diameter D1	23 mm	Handle Material	Zinc
Handle Color	Black	Insert and Screw Material	Steel
Insert and Screw Finish	Blackened	Weight (lbs)	0.637100
Manufacturer	JW Winco/ Otto Ganter	UPC	634529236475
Country of Origin	Germany	Tariff Code	8487.90.0080
UNSPC	31162807		

Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application.

Prop 65  **WARNING** This product can expose you to chemicals including Soots, Benzene, Lead, and Nickel (metallic), known to the State of California to cause cancer, and Lead and Benzene known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.