




JSC32-14-A

Ruland JSC32-14-A, 7/8" Jaw Coupling Hub, Aluminum, Set Screw Style With Keyway, 2.000" OD, 0.820" Length



Description

Ruland JSC32-14-A is a set screw zero-backlash jaw coupling hub with a 0.8750" bore, 3/16" keyway, 2.000" OD, and 0.820" length. It is a component in a three-piece design consisting of two aluminum hubs and an elastomeric insert called the spider creating a lightweight low inertia coupling capable of speeds up to 8,000 RPM. This three-piece design allows for a highly customizable coupling that easily combines clamp or set screw hubs with inch, metric, keyed, and keyless bores. Spiders are available in three durometers allowing the user to tailor coupling performance to their application. Ruland jaw couplings have a balanced design for reduced vibration at high speeds. Hardware is metric and tests beyond DIN 912 12.9 standards for maximum torque capabilities. JSC32-14-A is machined from bar stock that is sourced exclusively from North American mills and is RoHS3 and REACH compliant. It is manufactured in our Marlborough, MA factory under strict controls using proprietary processes.

Product Specifications

Bore (B1)	0.8750 in	Keyway (K)	3/16 in
B1 Max Shaft Penetration	0.820 in	Outer Diameter (OD)	2.000 in (50.8 mm)
Bore Tolerance	+0.001 in / -0.000 in	Hub Width (LH)	0.820 in
Length (L)	2.400 in (61.0 mm)	Recommended Shaft Tolerance	+0.0000 in / -0.0005 in
Forged Set Screw	M6	Number of Screws	2 ea 90° apart
Screw Material	Alloy Steel	Screw Finish	Black Oxide
Hex Wrench Size	3.0 mm	Seating Torque	7.2 Nm
Torque Specifications	Torque ratings vary with insert selection	Misalignment	Misalignment ratings vary with insert selection
Maximum Speed	8,000 RPM	Moment of Inertia	0.150858 lb-in ²
Full Bearing Support Required?	Yes	Recommended Inserts	JD32/51-98R , JD32/51-92Y
Zero-Backlash?	Yes	Balanced Design	Yes
Fail Safe?	Yes	Weight (lbs)	0.242300
Temperature	-10°F to 180°F (-23°C to 82°C)	Material Specification	2024-T351 Aluminum Bar
Finish	Bright	Finish Specification	Bright, No Plating
Manufacturer	Ruland Manufacturing	Recommended Gap Between Hubs	0.050 in (1.25 mm)
Country of Origin	USA	UPC	634529113462
UNSPC	31163011	Tariff Code	8483.60.8000
Note 1	Stainless steel hubs are available upon request.		
Note 2	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
Note 3	Torque ratings for the couplings are based on the physical limitations/failure point of the spiders. Under normal/typical conditions the hubs are capable of holding up to the nominal torque of the spiders. Please consult technical support for more assistance.		
Prop 65	 WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov .		

Installation Instructions

- Align the bores of the JSC32-14-A jaw coupling hubs on the shafts that are to be joined and determine if the misalignment parameters are within the limits of the coupling. (See spider for misalignment parameters.)
- Fully tighten the M6 screw(s) on the first hub to the recommended seating torque of 7.2 Nm using a

- 3.0 mm hex torque wrench.
3. Insert a spider into the jaws of one hub until the raised points contact the base of the hub.
 4. Insert the jaws of the second hub into the spider openings until the raised points contact the base of the second hub. Some force will be required to insert the second hub. This is normal.
 5. Assure that a gap is maintained between the two hubs so there is no metal to metal contact. Fully tighten the screw(s) on the second hub to the recommended seating torque.
-