




## RLC10-3-3-A

Ruland RLC10-3-3-A, 0.188" x 0.188" Long Slit Coupling, Aluminum, Clamp Style, 0.630" OD, 0.925" length



### Description

Ruland RLC10-3-3-A is a clamp style slit coupling with 0.1875" x 0.1875" bores, 0.630" OD, and 0.925" length. It is manufactured from a single piece of material and has two sets of intermittent slit cuts allowing for a maintenance-free coupling with high torsional stiffness in relation to comparable couplings, such as beam type. RLC10-3-3-A is commonly used in precise positioning applications found in semiconductor, medical, and test and measurement equipment. This long style slit coupling has added torque and misalignment capabilities compared to the short style. RLC10-3-3-A is zero-backlash, has a balanced design for reduced vibration at speeds up to 10,000 RPM, and can accommodate all forms of misalignment with light bearing loads. It is manufactured by Reliance Precision Ltd. in their County Cork, Ireland factory from 7075 aluminum for lightweight and low inertia. RLC10-3-3-A is inventoried by Ruland and RoHS3 and REACH compliant.

### Product Specifications

Bore (B1)	0.1875 in	Small Bore (B2)	0.1875 in
B1 Max Shaft Penetration	0.311 in	B2 Max Shaft Penetration	0.311 in
Outer Diameter (OD)	0.630 in	Bore Tolerance	+0.001 in / -0.000 in
Length (L)	0.925 in	Clearance Diameter (C) MAX	0.709 in
Cap Screw	M2	Screw Material	18-8 300 Series Stainless Steel
Hex Wrench Size	1.5 mm	Screw Finish	Bright
Seating Torque	0.36 Nm	Number of Screws	2
Dynamic Torque Reversing	4.9 lb-in	Angular Misalignment	2.5°
Dynamic Torque Non-Reversing	7.5 lb-in	Parallel Misalignment	0.008 in
Peak Torque	11 in-lb	Axial Motion	0.016 in
Torsional Stiffness	12.4 lb-in/Deg	Moment of Inertia	0.001228 lb-in <sup>2</sup>
Maximum Speed	10,000 RPM	Full Bearing Support Required?	Yes
Zero-Backlash?	Yes	Balanced Design	Yes
Material Specification	7075-T651 Extruded and Drawn Aluminum Bar	Temperature	-110°F to 175°F (-80°C to 80°C)
Finish Specification	SurTec 650	Manufacturer	Reliance Precision Limited
Country of Origin	Ireland	Weight (lbs)	0.022300
UPC	634529297995	Tariff Code	8483.60.8000
UNSPC	31163003		
Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
Prop 65			

 **WARNING** This product can expose you to the chemical Nickel (metallic), known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).