

FST-21A-2

✓ ACTIVE

TE Internal #: 3-1437186-4

Wire-to-Board Jumpers & Shunts, Flex-to-Board, 2 Position, .1 in [2.54 mm] Centerline, Length 25.4 mm [1 in], Wire & Cable

[View on TE.com >](#)



Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Jumpers & Shunts



Connector System: **Flex-to-Board**  
Number of Positions: **2**  
Centerline (Pitch): **2.54 mm [ .1 in ]**  
Product Length: **25.4 mm [ 1 in ]**  
Connector & Contact Terminates To: **Wire & Cable**

Features

Product Type Features

Compatible With Discrete Wire Type	Solid
Connector System	Flex-to-Board
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Conductors	2
Number of Rows	1
Number of Positions	2

Electrical Characteristics

Impedance	114 Ω
Operating Voltage	300 VAC

Body Features

Jumper Insulation Material	PTFE
----------------------------	------

Contact Features

Pin Arrangement (Left)	A
Pin Arrangement (Right)	A



Contact Current Rating (Max)	3 A
------------------------------	-----

Mechanical Attachment

Connector Mounting Type	Board Mount
-------------------------	-------------

Housing Features

Centerline (Pitch)	2.54 mm[.1 in]
--------------------	----------------

Dimensions

Wire Size	.204 mm²
Product Length	25.4 mm[1 in]

Usage Conditions

Operating Temperature Range	-40 – 150 °C[-40 – 302 °F]
-----------------------------	----------------------------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

FST-21A-2

Wire-to-Board Jumpers & Shunts, Flex-to-Board, 2 Position, .1 in [2.54 mm]  
Centerline, Length 25.4 mm [1 in], Wire & Cable



TE Part # 5-1437186-5  
FST-21A-8

TE Part # 3-1437186-5  
FST-21A-20

TE Part # 4-1437195-6  
FST-21A

TE Part # 2-1437186-9  
FST-21A-15

TE Part # 5-1437186-0  
FST-21A-5

Customers Also Bought

TE Part #1241050-4  
2x4P MOD II BREAK AWAY HDR,SMD, BLISTER

TE Part #641964-1  
02P UMN L PIN HDR ASSY POL 94VO

TE Part #1393219-3  
PE014005

TE Part #1217332-1  
187 FASTON,PCB TAB,TCBR

TE Part #320573  
PIDG R 22-16COMM 22-18MIL 3/8

TE Part #1-1318772-3  
025 12POS CAP ASSY H SELECTIVE-TIN

TE Part #5-1393224-1  
RY211048

TE Part #4602050003  
RPS-1-400/2.0-9

TE Part #1721181-5  
OJ-SS-112LMH2,005

Documents



Product Drawings

FST-21A-2

English

Product Specifications

Product Specification

English

Agency Approvals

UL Report

English