# 1612035-1 ✓ ACTIVE

### AMP | 0.64/025 Connector System


TE Internal #: 1612035-1

Housing for Male Terminals, Wire-to-Wire, 4 Position, .087 in [2.2 mm] Centerline, Natural, Signal, 0.64/025 Connector System

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > TH/.025 CONNECTOR SYSTEM, HOUSING



Connector System: Wire-to-Wire

Number of Positions: 4

Connector & Housing Type: Housing for Male Terminals

Centerline (Pitch): 2.2 mm [ .087 in ]

Sealable: No

### All TH/.025 CONNECTOR SYSTEM, HOUSING (192)

### **Features**

#### **Product Type Features**

Product Type Features	
Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Wire
Connector & Housing Type	Housing for Male Terminals
Sealable	No
Primary Locking Feature	On the Terminal
Configuration Features	
Blank Cavity Position	3
Number of Positions	4
Number of Rows	1
Electrical Characteristics	
Operating Voltage	12 VDC
Nominal Voltage Architecture	12 V
Body Features	
Cable Exit Angle	180°
Primary Product Color	Natural

**Contact Features** 



Contact Size	.64mm
Contact Type	Tab
Mating Tab Width	.64 mm[.025 in]
Mechanical Attachment	
Terminal Position Assurance	Yes
Strain Relief	Without
Mating Alignment Type	Polarized
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	PBT
Centerline (Pitch)	2.2 mm[.087 in]
Dimensions	
Connector Height	12.15 mm[.478 in]
Product Width	14 mm[.551 in]
Product Length	33.9 mm[1.335 in]
Usage Conditions	
Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C[158 °F][167 °F][176 °F][185 °F][194 °F] [212 °F][221 °F]
Operating Temperature Range	-30 - 105 °C[-22 - 221 °F]
Operation/Application	
Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94HB
Packaging Features	
Packaging Quantity	200
Packaging Method	Bag
Other	
Serviceable	Yes
Connector Position Assurance Capable	No



## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts





Also in the Series | 0.64/025 Connector System





Automotive Connector Caps & Covers (5)



Automotive Connector Locks & Position Assurance(1)



Automotive Housings(138)



Automotive Terminals(18)



Connector Seals & Cavity Plugs(1)



Other Automotive Connector Accessories(5)



PCB Headers & Receptacles(217)


## Customers Also Bought



TE Part # 61758-2 187 FASTON REC 20-16 AWG TPBR



TE Part # 2297911-1 12 WAY IN-LINE TAB PLUG ASSY



TE Part # 927783-3

JPT REC 2.8 Contact SRC Sn (LP)



TE Part # 1393449-1 V23540A1000Y452=VERSCHL.26P.



TE Part # 1-2203773-1 4POS, MCON 1.2 CB REC 1p TL SEALED



TE Part # 1-2299987-1 65W SEAL PLUG,CONN KIT



TE Part # 1732175-1 2+5 Sealed Connector Ass'y



RETAINER, TAB HSG., 49POSN.,



TE Part # 2324321-1 025 REC CONTACT



TE Part # 2329592-2 20POS,MQS,REC HSG,UNSLD

## **Documents**



### **Product Drawings**

025 G 4POS CAP W TO W

English

### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_1612035-1\_E.2d\_dxf.zip

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1612035-1\_E.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1612035-1\_E.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use.

### Datasheets & Catalog Pages

TH/.025 Connector Series

English

## **Product Specifications**

Crimping of 025 G Tab Contact

Japanese

**Application Specification** 

Japanese

CRIMPING 025 TH TAB CONTACT

Japanese

**Application Specification** 

Japanese