

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
APPLICATION STANDARD									
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO +85 °C			STORAGE TEMPERATURE RANGE	— °C TO — °C			
	VOLTAGE	100 V AC			OPERATING HUMIDITY RANGE	— % TO — %			
	CURRENT	0.4 A			APPLICABLE CABLE	—			
SPECIFICATIONS									
ITEM	TEST METHOD			REQUIREMENT			QT	AT	
CONSTRUCTION									
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING			<input type="radio"/>	<input type="radio"/>	
MARKING	CONFIRMED VISUALLY						<input type="radio"/>	—	
ELECTRICAL CHARACTERISTICS									
CONTACT RESISTANCE	100 mA (DC OR 1000 Hz)			45 mΩ MAX.			<input type="radio"/>	—	
CONTACT RESISTANCE	20 mV MAX, 1 mA (DC OR 1000 Hz)			55 mΩ MAX.			<input type="radio"/>	—	
MILLIVOLT LEVEL METHOD							<input type="radio"/>	—	
INSULATION RESISTANCE	250 V DC			100 MΩ MIN.			<input type="radio"/>	—	
VOLTAGE PROOF	300 V AC FOR 1 min.			NO FLASHOVER OR BREAKDOWN			<input type="radio"/>	—	
MECHANICAL CHARACTERISTICS									
CONTACT INSERTION AND EXTRACTION FORCES	BY STEEL GAUGE.			INSERTION FORCE: N MAX. EXTRACTION FORCE: N MIN.			—	—	
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.			INSERTION FORCE: (0.7 × * *) N MAX. WITHDRAWAL FORCE: (0.065 × * *) N MIN.			<input type="radio"/>	—	
MECHANICAL OPERATION	50 TIMES INSERTION AND EXTRACTIONS.			1) CONTACT RESISTANCE: 55 mΩ MAX. 2) NO DAMAGE, CRACK AND LOOSENESS OF PART.			<input type="radio"/>	—	
VIBRATION	FREQUENCY: 10 TO 55 Hz, SINGLE AMPLITUDE: 0.75 mm, - m/s ² AT 2 h FOR 3 DIRECTIONS.			1) NO ELECTRICAL DISCONTINUITY OF 1 μs 2) CONTACT RESISTANCE: 55 mΩ MAX. 3) NO DAMAGE, CRACK AND LOOSENESS OF PART.			<input type="radio"/>	—	
SHOCK	490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.						<input type="radio"/>	—	
ENVIRONMENTAL CHARACTERISTICS									
DAMP HEAT (STEADY STATE)	EXPOSED AT 40±2 °C, 90~95 %, 96 h.			1) CONTACT RESISTANCE: 55 mΩ MAX. 2) INSULATION RESISTANCE: 100 MΩ MIN. 3) NO DAMAGE, CRACK AND LOOSENESS OF PART.			<input type="radio"/>	—	
RAPID CHAGE OF TEMPERTURE	TEMPERTURE -55→+5→+35→+85→+5→+35 °C TIME 30→10~15→30→10~15 min. UNDER 5 CYCLES.						<input type="radio"/>	—	
DAMP HEAT,CYCLIC	EXPOSED AT %, TOTAL CYCLES(h).			1) CONTACT RESISTANCE: mΩ MAX. 2) INSULATION RESISTANCE: MΩ MIN.(AT HIGH HUMIDITY) 3) INSULATION RESISTANCE: MΩ MIN.(AT DRY) 4) NO DAMAGE, CRACK AND LOOSENESS OF PART.			—	—	
DRY HEAT	EXPOSED AT °C, h.			1) CONTACT RESISTANCE: mΩ MAX. 2) NO DAMAGE, CRACK AND LOOSENESS OF PART.			—	—	
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.			1) CONTACT RESISTANCE: 55 mΩ MAX. 2) NO HEAVY CORROSION.			<input type="radio"/>	—	
HYDROGEN SULPHIDE	EXPOSED IN 3 PPM FOR 96 h. (TEST STANDARD:JEIDA-38)						<input type="radio"/>	—	
SULPHUR DIOXIDE	EXPOSED IN PPM FOR h. (TEST STANDARD:JEIDA-39)						—	—	
RESISTANCE TO SOLDERING HEAT	SOLDER TEMPERATURE, °C FOR IMMERSION,DURATION, s.			NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINAL.			—	—	
SOLDABILITY	SOLDERED AT SOLDER TEMPERATURE, °C FOR IMMERSION DURATION, s.			A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSED.			—	—	
REMARKS	DRAWN		DESIGNED	CHECKED	APPROVED	RELEASED			
TO	<i>S. Morita</i>		<i>J. Matsukawa</i>	<i>M. Tomita</i>	<i>J. Yamashita</i>				
PCM	95.10.31		95.10.31	95.11.1	95.11.1				
UNLESS OTHERWISE SPECIFIED, REFER TO JIS C 5402.									
NOTE QT: QUALIFICATION TEST AT: ASSURANCE TEST <input type="radio"/> : APPLICABLE TEST									
HRS HIROSE ELECTRIC CO.,LTD.		SPECIFICATION SHEET			PART NO. FX8-***S-SV(21)				
CODE NO.(OLD) CL		DRAWING NO. SLC4-150730-01		CODE NO. CL 578 -	1 1				