

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				
APPLICABLE STANDARD									
RATING	OPERATING TEMPERATURE RANGE	-35 °C TO 85 °C(NOTE 1)			STORAGE TEMPERATURE RANGE	-10°C TO 60 °C			
	VOLTAGE	250 V AC			APPLICABLE CONNECTORS	DF1E-2022SC			
	CURRENT	AWG22~20 : 3A			OPERATING HUMIDITY RANGE	UL1007,1061:AWG22~20			
SPECIFICATIONS									
ITEM	TEST METHOD			REQUIREMENTS			QT	AT	
CONSTRUCTION									
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.			×	×	
MARKING	CONFIRMED VISUALLY.						×	×	
ELECTRIC CHARACTERISTICS									
CONTACT RESISTANCE	mA (DC OR 1000 Hz).			mΩ MAX			—	—	
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD.	20 mV MAX, 1 mA(DC OR 1000 Hz)			30 mΩ MAX.			×	—	
INSULATION RESISTANCE	500 V DC.			MΩ MIN			—	—	
VOLTAGE PROOF	650 V AC FOR 1 min.			NO FLASH OVER OR BREAKDOWN.			—	—	
MECHANICAL CHARACTERISTICS									
CONTACT INSERTION AND EXTRACTION FORCES	0.635 ± 0.002 BY STEEL GAUGE.			INSERTION FORCE 4.41 N MAX. EXTRACTION FORCE 0.29 N MIN.			×	—	
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.			INSERTION FORCE N MAX. EXTRACTION FORCE N MIN.			—	—	
MECHANICAL OPERATION	30 TIMES INSERTIONS AND EXTRACTIONS.			① CONTACT RESISTANCE: 30 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.			×	—	
VIBRATION	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75mm. — m/s² AT 2 h, FOR 3 DIRECTIONS.			① NO ELECTRICAL DISCONTINUITY OF 1μs. ② CONTACT RESISTANCE: 30 mΩ MAX.			×	—	
SHOCK	490 m/s² DIRECTIONS OF PULSE 11 ms AT 3 TIME FOR 3 DIRECTION.			③ NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.			×	—	
ENVIRONMENTAL CHARACTERISTICS									
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55 → 5 TO 35 → 85 → 5 TO 35 °C TIME 30 → 5 MAX → 30 → 5 MAX min UNDER 5 CYCLES.			① CONTACT RESISTANCE: 30 mΩ MAX. ② INSULATION RESISTANCE: 1000MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.			×	—	
DAMP HEAT (STEADY STATE)	EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.			① CONTACT RESISTANCE: 30 mΩ MAX. ② INSULATION RESISTANCE: MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.			×	—	
CORROSION SALT MIST	EXPOSED IN % SALT WATER SPRAY FOR h.			① CONTACT RESISTANCE: mΩ MAX. ② NO HAEAVY CORROSION.			—	—	
HYDROGEN SULPHIDE	EXPOSED IN — PPM FOR — h. (TEST STANDARD: JEIDA-38)			① CONTACT RESISTANCE: mΩ MAX. ② NO HAEAVY CORROSION.			—	—	
SULPHUR DIOXIDE	EXPOSED IN — PPM FOR — h. (TEST STANDARD: JEIDA-39)			① CONTACT RESISTANCE: mΩ MAX. ② NO HAEAVY CORROSION.			—	—	
SOLDERING HEAT	SOLDER TEMPERATURE, °C FOR IMMERSION, DURATION, S			NO DEFORMATION ON CASE OR EXCESSIVE LOOSENESS OF THE TERMINALS			—	—	
SOLDERABILITY	SOLDERED AT SOLDER TEMPERATURE, °C FOR IMMERSION DURATION, S.			SOLDER SHALL COVER MINIMUM OF 95 % OF THE SURFACE BEING IMMERSED.			—	—	
REMARKS NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT				DRAWN W. Fukuchi	DESIGNED W. Fukuchi	CHECKED C. Hanane	APPROVED K. Katayama	RELEASED	
Unless otherwise specified, refer to MIL-STD-1344.				99.11.12	99.11.12	99.11.12	99.11.12		
Note QT: Qualification Test AT: Assurance Test ×:Applicable Test									
HIROSE HIROSE ELECTRIC CO., LTD.		SPECIFICATION SHEET				PART NO. DF1E-2022SC			
CODE NO.(OLD) CL		DRAWING NO ELC4-161407			PEART NO CL541-1000-2			1 1	

