

APPLICABLE STANDARD		SPECIFICATIONS				
RATING	OPERATING TEMPERATURE RANGE OPERATING HUMIDITY RANGE	-35°C TO +85°C(NOTES 1) 20% TO 80%(NOTES 2)	STORAGE TEMPERATURE RANGE STORAGE HUMIDITY RANGE	-10°C TO +60°C(NOTES 3) 40% TO 70%(NOTES 2)(NOTES 3)		
	VOLTAGE		APPLICABLE CONNECTOR	DF81-30S-0.4H(##)		
	CURRENT		APPLICABLE CABLE			
CONSTRUCTION		ITEM	TEST METHOD	REQUIREMENTS	QT AT	
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	X X	
MARKING		CONFIRMED VISUALLY.			X X	
△	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
REMARKS NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT NOTE2: NON CONDENSING NOTE3: THE TERM "STORAGE" REFERS TO PRODUCTS STORED FOR A LONG PERIOD PRIOR TO MOUNTING AND USE. THE OPERATING TEMPERATURE AND HUMIDITY RANGE COVERS THE NON-CONDUCTING CONDITION OF CONNECTORS AFTER BOARD MOUNTING AND THE TEMPORARY STORAGE CONDITIONS OF TRANSPORTATION, etc Unless otherwise specified, refer to JIS C 5402, IEC60512.				APPROVED	TS. SAKATA	12. 11. 12
				CHECKED	HS. OZAWA	12. 11. 12
				DESIGNED	TP. MATSUMOTO	12. 11. 09
				DRAWN	TP. MATSUMOTO	12. 11. 09
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC4-340821-01	
	SPECIFICATION SHEET		PART NO.	DF81-30P-LCH		
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL662-8107-3-00	△	1/1