

Part Number : 877970400

Series Number : 87797

Product Category : PCB Headers and Receptacles

Product Description : C-Grid Header, Through Hole, Dual Row Dual Body, Vertical, 0.38µm Gold (Au) Plating, 12.70mm Stacking Height, Tray Packaging, 40 Circuits, Lead-Free

Status : Active

## Documents & Resources

### Drawings

Drawing 877970400\_sd.pdf

Packaging Design Drawing PK-87797-300-000.pdf

Packaging Design Drawing PK-89990-489-001.pdf

### 3D Models and Design Files

3D Model 877970400\_stp.zip

### Specifications

Application Specification 713080001-AS-000.pdf

Product Specification PS-87920-019-001.pdf

Test Summary 879200000-TS-000.pdf

Test Summary 879200001-TS-000.pdf

## Product Environment Compliance

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Relevant
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

## Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

---

### **Part Details**

#### **General**

Status	Active
Category	PCB Headers and Receptacles
Series	87797
Description	C-Grid Header, Through Hole, Dual Row Dual Body, Vertical, 0.38µm Gold (Au) Plating, 12.70mm Stacking Height, Tray Packaging, 40 Circuits, Lead-Free
Application	Board-to-Board, Signal
Component Type	PCB Header
Product Family	C-Grid Connector Products
Product Name	C-Grid,Dual Body
UPC	822350598705

#### **Agency**

UL	E29179
----	--------

#### **Electrical**

Current - Maximum per Contact	3.0A
Voltage - Maximum	250V

#### **Physical**

Breakaway	Yes
Circuits (Loaded)	40
Circuits (maximum)	40
Color - Resin	Black
First Mate / Last Break	No

Flammability	94V-0
Glow-Wire Capable	No
Guide to Mating Part	No
Keying to Mating Part	None
Lock to Mating Part	None
Material - Metal	Copper Alloy
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Net Weight	5.025/g
Number of Rows	2
Orientation	Vertical
Packaging Type	Tray
PC Tail Length	2.79mm
PCB Locator	No
PCB Retention	None
PCB Thickness - Recommended	1.60mm
Pitch - Mating Interface	2.54mm
Pitch - Termination Interface	2.54mm
Plating min - Mating	0.381µm
Plating min - Termination	2.032µm
Polarized to Mating Part	No
Polarized to PCB	No
Shrouded	No
Stackable	No
Temperature Range - Operating	-55° to +105°C
Termination Interface Style	Through Hole

## Solder Process Data

Max-Duration	14
Lead-Free Process Capability	WAVE
Max-Cycle	1
Max-Temp	265

---

This document was generated on May 24, 2024