




Connectors > Power Connectors > Circular Power > Circular Power Connectors > Connectors with Posted Pin Contacts, CPC Series 1



Connector Product Type: **Connector Assembly**
Operating Voltage: **250 VDC**
Connector System: **Wire-to-Board, Wire-to-Panel**
Number of Positions: **9**
Sealable: **Yes**

[All Connectors with Posted Pin Contacts, CPC Series 1 \(39\)](#)

Features

Product Type Features

Connector Product Type	Connector Assembly
Connector System	Wire-to-Board, Wire-to-Panel
Sealable	Yes
Connector & Housing Type	Receptacle
Circular Connector Shell Type	All Plastic

Configuration Features

Number of Positions	9
Number of Power Positions	0
Number of Signal Positions	9

Electrical Characteristics

Operating Voltage	250 VAC
-------------------	---------

Contact Features

--	--



Reverse Gender	Yes
----------------	-----

Contact Type	Socket
--------------	--------

Termination Features

Termination Method to Printed Circuit Board	Through Hole - Solder
---	-----------------------

Mechanical Attachment

Mating Alignment Type	Keyed
-----------------------	-------

Mating Alignment	With
------------------	------

Panel Mount Feature Type	Flange with Mounting Holes
--------------------------	----------------------------

Mating Retention Type	Threaded Coupling
-----------------------	-------------------

Polarization Code	A
-------------------	---

Connector Mounting Type	Panel Mount
-------------------------	-------------

Mating Retention	With
------------------	------

Panel Mount Feature	With
---------------------	------

Housing Features

Housing Color	Black
---------------	-------

Housing Material	PA 6.6
------------------	--------

Circular Connector Shell Size	17
-------------------------------	----

Dimensions

Assembly Length	32.26 mm[1.27 in]
-----------------	-------------------

Usage Conditions

Operating Temperature Range	-55 - 105 °C[-67 - 221 °F]
-----------------------------	----------------------------

Fluid Resistance	Immersion
------------------	-----------

Operation/Application

Circuit Application	Signal
---------------------	--------

Shielded	No
----------	----

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Quantity	24
--------------------	----

Packaging Method	Tray
------------------	------

Product Compliance






For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 207299-3 FLANGE PLUG MOUNT CPC	 TE Part # CAT-AM71-C83998B CPC Cable Clamps	 TE Part # 211768-1 CPC PLUG ASSEMBLY SIZE 17-9	 TE Part # 207241-1 CABLE BOOT, SZ 17, CPC
 TE Part # 207387-1 CABLE GRIP, SZ 17, CPC	 TE Part # 207387-2 CABLE GRIP, SZ 17, CPC	 TE Part # 4-2407269-1 CAP, CPC, SIZE 17 RECP, ORANGE	 TE Part # 4-2407269-4 CAP, CPC, SIZE 17 RECP, YELLOW




TE Part # 4-2407269-3
CAP, CPC, SIZE 17 RECP, RED




TE Part # 4-2407269-2
CAP, CPC, SIZE 17 RECP, BLACK


Also in the Series | AMP CPC




Circular Power Connectors(458)



Connector Backshells(2)



Connector Caps & Covers(16)




Connector Contacts(6)




Connector Hardware(12)




Connector Seals & Cavity Plugs(36)



Connector Strain Relief(60)



Insertion & Extraction Tools(1)



Sealing Sleeves(2)

Customers Also Bought




TE Part # 1-1564512-1
8POS, TAB 1.6X0.6, TAB HSG, ASSY



TE Part # 4-2176231-9
3522 1K0 1% 3W



TE Part # 3-794620-4
04P MICRO MNL ASSY, R/A, HDR, LF



TE Part # 1586037-2
2P VERT HDR VAL-U-LOK V2



TE Part # 796500-2
CPC POSTED RCPT,13-7,R/A

TE Part # 1-2176092-8
RP 2A 0.25W 1K0 0.1% 25PPM 1K RL

TE Part # 2-2176349-5
CRGCQ 2512 1K0 1%

TE Part # 102320-1
UNIVERSAL HEADER LATCH

TE Part # 1-796642-0
10POS 5.0MM CE VRT HDR,TRM BLK

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-213826-1_Z.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-213826-1_Z.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-213826-1_Z.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

AMP Circular Connectors for Commercial Signal & Power Applications

English

Product Specifications

Application Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English

Instruction Sheet (U.S.)

English



[Agency Approvals](#)

[CSA Certificate](#)

English