

V23101D 106B201

✓ ACTIVE

Axicom | Axicom W11 Relay V23101


TE Internal #: 3-1393779-3

Signal Relays, 120 VDC Contact Voltage, 125 VAC Contact Voltage,
203mW Coil Power Rating DC, Printed Circuit Board, Axicom W11
Relay V23101

[View on TE.com >](#)



Relays & Contactors > Relays > Signal Relays



Contact Voltage Rating: 120 VDC
Coil Power Rating DC: 203 mW
Product Mount Type: Printed Circuit Board
Coil Voltage Rating: 24 VAC

Features

Configuration Features

Contact Arrangement	2 Form C (CO)
Contact Number of Poles	1

Electrical Characteristics

Insulation Initial Dielectric Between Open Contacts	750 Vrms
Contact Limiting Making Current	1.25 A
Contact Limiting Short-Time Current	1.25 A
Contact Limiting Continuous Current	1.25 A
Insulation Initial Dielectric Between Contacts & Coil	1000 Vrms
Insulation Initial Resistance	1000000 MΩ
Power Consumption	200 mW
Contact Limiting Breaking Current	1.25 A
Contact Switching Load (Min)	10mA @ .02V
Coil Resistance	700 Ω
Contact Voltage Rating	120 VDC
Coil Power Rating DC	203 mW
Coil Voltage Rating	12 VDC
Contact Current Rating	2 A
Contact Switching Voltage (Max)	120 VDC

Body Features



Product Weight	4 g[.141 oz]
----------------	--------------

Contact Features

Contact Plating Material	Gold
Contact Material	Silver Palladium (AgPd) Alloy

Termination Features

Relay Connection Type	PCB Termination
Terminal Configuration	PCB Pins

Mechanical Attachment

Product Mount Type	Printed Circuit Board
--------------------	-----------------------

Dimensions

Product Width	10 mm[.393 in]
Product Length	15.4 mm[.606 in]
Product Height	11.5 mm[.452 in]

Usage Conditions

Environmental Ambient Temperature (Max)	85 °C[85 °F]
Operating Temperature Range	-40 - 85 °C

Operation/Application

Actuating System	DC
Solder Process	Wave Solder
Performance Type	Standard
Coil Magnetic System	Monostable, DC

Packaging Features

Packaging Method	Box & Tube, Tube
------------------	------------------

Other

Length Class (Mechanical)	14 - 16 mm
Environmental Ambient Temperature Class	70 - 85 °C
Height Class (Mechanical)	11 - 12 mm
Coil Power Rating Class	200 - 300 mW
Width Class (Mechanical)	10 - 12 mm
Contact Current Class	0 - 2 A

Product Compliance



For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 1-1393779-6
V23101D 6B201



TE Part # 4-1393779-2
V23101D1006B201

Also in the Series | Axicom W11 Relay V23101



Signal Relays(25)

Customers Also Bought



TE Part # 1-1623729-9
BCHE 17 W 3R3 10%



TE Part # 280374-2
10P AMPMODU II SHRD HDR, ST, 0.38 AU




TE Part # 5-146254-3
06 MODII HDR DRST B/A .100CL



TE Part # 6-1393243-8
RT424024



TE Part # 2834167-3
RELEASABLE SLIM CONTACT




TE Part # 2106091-1
2 pos Inverted Thru Board SMT Header



TE Part # 2834172-3
ULTRAMINIATURE SLIM MALE PIN CONTACT



TE Part # 6-2176088-7
RP 1J 0.166W 4K32 0.1% 25PPM 1K RL



TE Part # 2176316-1
MELF SMA_A 100R 0.1% 15PPM 0207 1W



TE Part # ANT-868-JJB-RA
Antenna Mini R-Angle 868MHz THM

Documents

CAD Files

Customer View Model

[ENG_CVM_CVM_3-1393779-3_B1.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_3-1393779-3_B1.3d_stp.zip](#)

English

Customer View Model

[ENG_CVM_CVM_3-1393779-3_B1.2d_dxf.zip](#)



English

3D PDF

3D

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Product Specification

English

Definitions General Purpose Relays

English