

2-2106003-3 ACTIVE

LUMAWISE | Insulation Displacement Connectors Closed End

TE Internal #: 2-2106003-3

Poke-In Connectors, Wire-to-Board, 3 Position, 4 in [.16 mm]


Centerline, Printed Circuit Board, Insulation Displacement

Connectors Closed End

[View on TE.com >](#)



Connectors > Lighting Connectors > Poke-In Connectors



Connector System: **Wire-to-Board**

Number of Positions: **3**

Centerline (Pitch): **.16 mm [4 in]**

Connector & Contact Terminates To: **Printed Circuit Board**

Connector Height: **.23 mm [5.8 in]**

Features

Product Type Features

| | |
|------------------|---------------|
| Connector System | Wire-to-Board |
|------------------|---------------|

| | |
|-----------------------------------|-----------------------|
| Connector & Contact Terminates To | Printed Circuit Board |
|-----------------------------------|-----------------------|

Configuration Features

| | |
|---------------------|---|
| Number of Positions | 3 |
|---------------------|---|

Contact Features

| | |
|------------------------------|-----|
| Contact Current Rating (Max) | 7 A |
|------------------------------|-----|

Termination Features

| | |
|---|---------------|
| Termination Method to Printed Circuit Board | Surface Mount |
|---|---------------|

Mechanical Attachment

| | |
|-------------------------|-------------|
| Connector Mounting Type | Board Mount |
|-------------------------|-------------|

Housing Features

| | |
|--------------------|--------------|
| Centerline (Pitch) | .16 mm[4 in] |
|--------------------|--------------|

Dimensions

| | |
|------------------|----------------|
| Connector Height | .23 mm[5.8 in] |
|------------------|----------------|

| | |
|-----------|-------------|
| Wire Size | 22 - 20 AWG |
|-----------|-------------|

Usage Conditions

| | |
|-----------------------------|----------------------------|
| Operating Temperature Range | -40 - 105 °C[-40 - 221 °F] |
|-----------------------------|----------------------------|

Operation/Application

| | |
|---------------------|-------|
| Circuit Application | Power |
|---------------------|-------|

Product Compliance

For compliance documentation, visit the product page on [TE.com](https://te.com)>

| | |
|---|---|
| EU RoHS Directive 2011/65/EU | Compliant |
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC |
| Halogen Content | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free |
| Solder Process Capability | Reflow solder capable to 245°C |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




TE Part # 2-2106431-3
Connector, SMT-IDC PASS THRU, 3
POS, 22


TE Part # 6-2106003-3
Connector, SMT-IDC, 3 pos, 22AWG,
black

Also in the Series

Insulation Displacement Connectors Closed End



Ballast Connectors(23)



Board-In Connectors(9)



PCB Headers & Receptacles(1)



Poke-In Connectors(66)

Customers Also Bought



TE Part # EEC-325X4B-E016
ENCLOSURE, 3.25 X 4, CLR, NO VENT



TE Part # WM-3P
WEDGE LOCK, 3P, REC, ORG, DTM



TE Part # 1-2273122-1
M12 angled plug to M12 strgt socket
AA



TE Part # 1-2106431-4
Connector, SMT-IDC PASS THRU, 4
POS, 20



TE Part # 2-2106431-4
Connector, SMT-IDC PASS THRU, 4
POS, 22



TE Part # DTM06-3S-E007
DEUTSCH DTM Housings



TE Part # CX7201-000
RHW-180/50-1200/ADH-0



TE Part # 10218853-00
PRESS XDCR M325M-00000E-010BG

Documents

Product Drawings

[Connector, SMT-IDC, 3 position, 22AWG](#)

English

CAD Files

[3D PDF](#)

3D

[Customer View Model](#)

[ENG_CVM_CVM_2-2106003-3_B.2d_dxf.zip](#)

English

[Customer View Model](#)

[ENG_CVM_CVM_2-2106003-3_B.3d_igs.zip](#)

English

[Customer View Model](#)

[ENG_CVM_CVM_2-2106003-3_B.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[IDC_SSL_CONNECTOR](#)

English

Product Specifications

[Application Specification](#)

English

Agency Approvals

[Agency Approval Document](#)

English