




Connectors > PCB Connectors > PCB Headers & Receptacles



Connector System: **Wire-to-Board**

Number of Positions: **2**

Number of Rows: **1**

Centerline (Pitch): **3.96 mm [.156 in]**

PCB Mount Orientation: **Vertical**

Features

Product Type Features

Connector Shape	Rectangular
Connector System	Wire-to-Board
Header Type	Partially Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
PCB Connector Assembly Type	PCB Mount Header

Configuration Features

Number of Power Positions	2
Number of Loaded Positions	2
Number of Positions	2
Number of Rows	1
PCB Mount Orientation	Vertical

Electrical Characteristics

Operating Voltage	250 VAC
-------------------	---------



Body Features

Primary Product Color	Natural
-----------------------	---------

Contact Features

Contact Mating Area Length	7.7 mm[.303 in]
PCB Contact Termination Area Plating Material Thickness	3.04 µm[120 µin]
Contact Layout	Inline
Contact Underplating Material Thickness	1 µm[39.37 µin]
Contact Mating Area Plating Material Thickness	3.04 µm[120 µin]
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Brass
Contact Mating Area Plating Material	Tin
Contact Type	Tab
Contact Current Rating (Max)	8 A

Termination Features

Termination Post & Tail Length	3.69 mm[.145 in]
Termination Method to Printed Circuit Board	Through Hole - Solder

Mechanical Attachment

PCB Mount Alignment Type	Pegs
Mating Retention	With
Mating Retention Type	Locking Tab
Connector Mounting Type	Board Mount
Mating Alignment	Without
PCB Mount Alignment	With
PCB Mount Retention	Without

Housing Features

Housing Material	Nylon
Centerline (Pitch)	3.96 mm[.156 in]

Dimensions

Connector Length	7.92 mm[.312 in]
Connector Height	9.4 mm[.37 in]
Connector Width	8.6 mm[.339 in]



PCB Thickness (Recommended)	1.6 mm[.063 in]
-----------------------------	-----------------

Usage Conditions

Operating Temperature (Max)	105 °C[221 °F]
Operating Temperature Range	-30 - 105 °C[-22 - 221 °F]

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

Glow Wire Rating	GWT 750°C (Without Flame)
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Quantity	1000
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>



Compatible Parts

 TE Part # 1-1123722-2 3.96 EP PLUG HSG 2P(NATURAL)	 TE Part # 1744544-2 EP II TPA 02P, BLACK	 TE Part # 1-1744429-6 3.96 EP HDR ASSY 6P W/PEGS, GW, NO PIN 3	 TE Part # 1-1744429-9 3.96 EP HDR ASSY 9P W/PEGS, GW, NO PIN 3
 TE Part # 1-1744524-0 EP 10P HEADER ASY NO 8 PIN	 TE Part # 1-1744524-1 EP 11P HEADER ASY NO 6,10 PINS	 TE Part # 1-1744524-2 EP 12P HEADER ASY NO 2,6 PINS	 TE Part # 2-1744435-8 EP 08P V-HDR ASY NO 3 PIN
 TE Part # 2-1744524-5 EP 05P HEADER ASY NO 2,3,4 PIN			

Also in the Series | Economy Power

 Connector Contacts(15)	 Connector Hardware(2)	 Insertion & Extraction Tools(1)	 PCB Headers & Receptacles(399)
---	---	--	---



Rectangular Connector Housings(1)



Rectangular Power Connectors(64)




Wire-to-Board Connector Assemblies & Housings(142)

Customers Also Bought



TE Part # 4-440052-5
2.5MM,HDR,5POS,VERTICAL, CONNECTOR




TE Part # 2029181-5
5P VAL-U-LOK VRTHDR W/PGS GW



TE Part # 1-1123723-0
3.96 EP HDR ASSY 10P(NATURAL)



TE Part # 4-1123724-3
3.96EP HDR ASSY 3(5)P RED



TE Part # 2029181-4
4P VAL-U-LOK VRTHDR W/PGS GW



TE Part # 2309279-3
03P EP SHRD HDR ASY,NO 2 PIN, WHITE



TE Part # 2309279-8
08P EP SHRD HDR ASY,NO 7 PIN, WHITE



TE Part # 2322950-6
6P, RAST 5 TAB HEADER SELEC, THV, OPP

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1744429-2_D.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1744429-2_D.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1744429-2_D.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

Economy Power II (EP II) Glow Wire test compliant connectors

English



1-1773885-9 Economy Power Connectors

English

Product Specifications

Application Specification

Japanese