

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: UK Plug (Type G), BS1363A, Fused at 10A to IEC320-C13, GT Cable #427: 1.0mmsq / 3 Conductors, 7.1mm OD, H05VV-F, 70 Deg.C, 500V, BLU/BRN/GRN-YW, Approvals: EN 50525-2-11; IEC 60227, 2500mm, GlobTek Black		
	Model No. Power Cord		
	Part No./Ordering No. PZ0800100-2M5BK13H(R)		Rev N

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

In Addition to GlobTek Inc.'s renewed ISO9001:2008 - Quality Management System Certification, GlobTek Inc. is now certified to:

ISO13485:2003 - Medical Devices Quality Management System Certification

ISO14001:2004 - Environmental Management System Certification

ISO Certificates are available online at <https://www.globtek.com/iso-certificates/>
Prop 65 Statement:<https://en.globtek.com/prop-65-statement.pdf>

The acceptance of this specification and use of the product described in this document indicates the acceptance and binding of the customer to Globtek TERMS AND CONDITIONS (attached to the end of this document), which supersede all other agreements, terms, and conditions (<https://en.globtek.com/terms-and-conditions/>).

The purchaser of this product (Customer) agrees that it is their sole responsibility to determine suitability/fitness of the product described in this specification for their application and to take precautions for protection against any hazards attendant to the handling and use of the product.

Footnote:

GlobTek Inc. will not be liable for the safety and performance of these power supplies if unauthorized access and repair occurs. End user should consult applicable UL, CSA or EN standards for proper installation instruction.

Limitation of Use:

GlobTek products are intended for use with commercial, medical, and/or industrial equipment only. GlobTek product are not authorized for use as mission critical components in life support hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of GlobTek Inc.
Contents of this document are subject to change without prior notice.

Customer Approval of Specification:

Please approve, sign and send back to GlobTek so we can complete order processing.
A delay in receipt of this form will delay delivery schedule.

Company Name:

Quote Number:

Authorized Representative Name:

Customer P/N:

Date:

Authorized Representative Signature:

PROPRIETARY INFORMATION

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC. © GlobTek, Inc.

2012 - 2024

quest /06/02/2024 2:53:43 AM

Page 1 of 7

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: UK Plug (Type G), BS1363A, Fused at 10A to IEC320-C13, GT Cable #427: 1.0mmsq / 3 Conductors, 7.1mm OD, H05VV-F, 70 Deg.C, 500V, BLU/BRN/GRN-YW, Approvals: EN 50525-2-11; IEC 60227, 2500mm, GlobTek Black		
	Model No. Power Cord		
	Part No./Ordering No. PZ0800100-2M5BK13H(R)		Rev N

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

REVISION HISTORY

REV	DESCRIPTION	SUB	DATE	APPROVED
N	Add UKCA and CE marking to the IEC320/C13 connector	bsiep	07/15/2021	QA
M	Update to SF format; add Singapore, Malaysia, Hong Kong, Saudi Arabia, and Gulf States approvals. Connector approval updated from individual EU approvals to ENEC-VDE.	bsiep	10/09/2020	QA
L	UPDATE ASTA LICENSE	jsund	02/02/2012	QA


Cordset Information:
CordsetColor:GlobTek Black
Cord Length (mm):2500

NOTES:

BS 1363A fused @ 10A


GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: UK Plug (Type G), BS1363A, Fused at 10A to IEC320-C13, GT Cable #427: 1.0mmsq / 3 Conductors, 7.1mm OD, H05VV-F, 70 Deg.C, 500V, BLU/BRN/GRN-YW, Approvals: EN 50525-2-11; IEC 60227, 2500mm, GlobTek Black	
	Model No. Power Cord	
	Part No./Ordering No. PZ0800100-2M5BK13H(R)	Rev N

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE



GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: UK Plug (Type G), BS1363A, Fused at 10A to IEC320-C13, GT Cable #427: 1.0mmsq / 3 Conductors, 7.1mm OD, H05VV-F, 70 Deg.C, 500V, BLU/BRN/GRN-YW, Approvals: EN 50525-2-11; IEC 60227, 2500mm, GlobTek Black	
	Model No. Power Cord	
	Part No./Ordering No. PZ0800100-2M5BK13H(R)	Rev N

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE



GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: UK Plug (Type G), BS1363A, Fused at 10A to IEC320-C13, GT Cable #427: 1.0mmsq / 3 Conductors, 7.1mm OD, H05VV-F, 70 Deg.C, 500V, BLU/BRN/GRN-YW, Approvals: EN 50525-2-11; IEC 60227, 2500mm, GlobTek Black	
	Model No. Power Cord	Part No./Ordering No. PZ0800100-2M5BK13H(R)


End A	Cable	End B
Code:PZ0800	Code:427	Code:701-VDE-ENEC-CE-UKCA
Description:UK Plug (Type G), BS1363A, Fused at 10A	Description:GT Cable #427: 1.0mmsq / 3 Conductors, 7.1mm	Description:IEC320-C13
Rating (V):250	OD, H05VV-F, 70 Deg.C, 500V, BLU/BRN/GRN-YW,	Rating (V):250
Rating (A):10.0	Approvals: EN 50525-2-11; IEC 60227	Rating (A):10.0
Gender:Male	Color:GlobTek Black	Gender:Female
Overmolded:Yes	Wire Gauge(AWG):1.0mmsq	Overmolded:Yes
	Cond:3	
	Type:H05VV-F	
	Temperature:70° C	
	Amps:10	
	Volts:500	
	OD:7.1	
	ConductorsColors:BLU/BRN/GRN-YW	

Plug Approvals	Cable Approvals	Connector Approvals
 United Kingdom ASTA Diamond Approval Mark  SAFETY MARKS Singapore PMS safety mark  Hong Kong HK safety mark Saudi Arabia SASO safety mark (file # only -- SASO 2203) Malaysia (File number)  Gulf Conformity mark	 EAC CHINA  D  N  S  FI   OVE  KEMA  CE  VDE  UL 15324P	 EN EC 10  VDE ENEC-VDE  UK CA UKCA Certification  CE CE Certification

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: UK Plug (Type G), BS1363A, Fused at 10A to IEC320-C13, GT Cable #427: 1.0mmsq / 3 Conductors, 7.1mm OD, H05VV-F, 70 Deg.C, 500V, BLU/BRN/GRN-YW, Approvals: EN 50525-2-11; IEC 60227, 2500mm, GlobTek Black	
	Model No. Power Cord	
	Part No./Ordering No. PZ0800100-2M5BK13H(R)	Rev N

CUSTOMIZED LENGTHS, COLORS, CABLE TYPES, TERMINATIONS/PLUGS/RECEPTACLES AVAILABLE UPON REQUEST. ADDITIONAL PLUG OPTIONS ARE AVAILABLE AT <https://www.globtek.com/connectors/> STANDARD PLUGS AND CONNECTORS CAN BE SEEN ONLINE AT <https://www.globtek.com/connectors/> ACTUAL CONNECTORS, OVERMOLDS, FERRITES MAY VARY SLIGHTLY FROM THE PICTURE BELOW DIMENSIONS ARE IN MM UNLESS SPECIFIED OTHERWISE

Hanking:200
Description:200 +/- 20mm
Image:



Notes/Modifications/Customizations (notes in this section supersede the values shown in the standard spec):