

LIT 1X2-24 - Surge protection device



2804610

<https://www.phoenixcontact.com/us/products/2804610>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Surge protection in a one-piece 6.2 mm wide DIN rail module for one floating signal circuit in 2-conductor technology. Tested in accordance with the following types of protection in Ex areas: Ex ia IIC / Ex iaD. HART-compatible.

Your advantages

- Space saving with a narrow overall width of just 6 mm
- Cost-optimized with tailored product features
- Universal use with extended nominal voltage range

Commercial data

Item number	2804610
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	CL02
Product key	CL2211
Catalog page	Page 124 (C-4-2019)
GTIN	4046356428330
Weight per piece (including packing)	64.86 g
Weight per piece (excluding packing)	53 g
Customs tariff number	85363010
Country of origin	DE

LIT 1X2-24 - Surge protection device

2804610

<https://www.phoenixcontact.com/us/products/2804610>



Technical data

Product properties

Product type	Surge protection for MCR technology
Product family	LINETRAB
IEC test classification	C1
	C2
	C3
	D1
Type	DIN rail module, one-piece
Wire pairs per module	1

Insulation characteristics

Overvoltage category	III
Pollution degree	2

Electrical properties

Nominal voltage U_N	24 V DC
-----------------------	---------

Connection data

Connection method	Screw connection
Screw thread	M3
Tightening torque	0.8 Nm
Conductor cross section flexible	0.2 mm² ... 2.5 mm²
Conductor cross section rigid	0.2 mm² ... 2.5 mm²
Conductor cross section AWG	24 ... 14

Ex data

Maximum inner capacitance C_i	typ. 1.3 nF
Max. internal inductance L_i	< 1 µH
Max. input current I_i	350 mA (T4 / ≤ 80 °C)
	200 mA (T5 / ≤ 50 °C)
	150 mA (T6 / ≤ 40 °C)
Max. input voltage U_i	36 V DC
max. input power P_i	3.00 W
Maximum inner time factor (R_i/L_i)	0.2 µs

Dimensions

Dimensional drawing	
---------------------	--

LIT 1X2-24 - Surge protection device



2804610

<https://www.phoenixcontact.com/us/products/2804610>

Width	6.2 mm
Height	93.1 mm
Depth	102.5 mm (incl. DIN rail 7.5 mm)

Material specifications

Color	anthracite grey (RAL 7016)
Flammability rating according to UL 94	V-0
Insulating material	PBT
Housing material	PBT

Mechanical properties

Mechanical data

Open side panel	No
-----------------	----

Protective circuit

Direction of action	Line-Line & Line-Earth Ground
Maximum continuous voltage U_C	36 V DC
	25 V AC
Rated current	350 mA (40 °C)
Operating effective current I_C at U_C	$\leq 2 \mu A$
Residual current I_{PE}	$\leq 2 \mu A$
Nominal discharge current I_n (8/20) μs (line-line)	5 kA
Nominal discharge current I_n (8/20) μs (line-ground)	5 kA
Pulse discharge current I_{imp} (10/350) μs (line-earth)	500 A
	1 kA (in total)
Total discharge current I_{total} (8/20) μs	10 kA
	20 kA (1x)
Max. discharge current I_{max} (8/20) μs maximum (line-line)	10 kA
Max. discharge current I_{max} (8/20) μs maximum (line-earth)	10 kA
	20 kA (in total)
Nominal pulse current I_{an} (10/1000) μs (line-line)	50 A
Nominal pulse current I_{an} (10/1000) μs (line-earth)	50 A
	100 A (in total)
Output voltage limitation at 1 kV/ μs (line-line) spike	$\leq 60 V$
Output voltage limitation at 1 kV/ μs (line-earth) spike	$\leq 650 V$
Residual voltage at I_n (conductor-conductor)	$\leq 70 V$
Residual voltage with I_{an} (10/1000) μs (line-line)	$\leq 50 V$
Voltage protection level U_p (line-line)	$\leq 70 V$ (C2 - 10 kV / 5 kA)
	$\leq 50 V$ (C3 - 10 A)
	$\leq 55 V$ (C3 - 50 A)
Voltage protection level U_p (line-earth)	$\leq 650 V$ (C1 - 500 V / 250 A)
	$\leq 700 V$ (C2 - 10 kV / 5 kA)
	$\leq 650 V$ (C3 - 10 A)
	$\leq 700 V$ (C3 - 50 A)

LIT 1X2-24 - Surge protection device



2804610

<https://www.phoenixcontact.com/us/products/2804610>

Response time t_A (line-line)	≤ 1 ns
Response time t_A (line-earth)	≤ 100 ns
Input attenuation aE, sym.	typ. 0.7 dB (1 MHz/50 Ω) typ. 0.3 dB (350 kHz/150 Ω)
Cut-off frequency f_g (3 dB), sym. in 50 Ω system	typ. 6 MHz
Cut-off frequency f_g (3 dB), sym. in 150 Ω system	typ. 2 MHz
Capacity	≤ 1.3 nF (per channel)
Resistance per path	3.3 $\Omega \pm 20$ %
Surge protection fault message	none
Max. required back-up fuse	315 mA (T)
Impulse durability (line-line)	C2 - 10 kV / 5 kA C3 - 50 A
Impulse durability (line-earth)	C1 - 1 kV / 500 A C2 - 10 kV / 5 kA C3 - 50 A D1 - 500 A
Alternating current carrying capacity (line-earth)	5 A - 1 s

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 80 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	≤ 2000 m (amsl)

Approvals

Conformity/Approvals

ATEX	II 1 G Ex ia IIC T4...T6 II 1 D Ex iaD 20 T85°C...135°C
IECEx	Ga Ex ia IIC T4...T6 Ex iaD 20 T85 °C...T135 °C

Standards and regulations

Standards/specifications	EN 61643-21
Note	A2:2013
Standards/specifications	EN 60079-0
Note	2018
Standards/specifications	EN 60079-11
Note	2012
Standards/specifications	IEC 60079-0
Note	2017
Standards/specifications	IEC 60079-11
Note	2011

LIT 1X2-24 - Surge protection device



2804610

<https://www.phoenixcontact.com/us/products/2804610>

Mounting

Mounting type	DIN rail: 35 mm
---------------	-----------------

LIT 1X2-24 - Surge protection device


2804610

<https://www.phoenixcontact.com/us/products/2804610>




Drawings

Dimensional drawing



Application drawing




LIT 1X2-24 - Surge protection device

2804610


<https://www.phoenixcontact.com/us/products/2804610>



Diagram



Circuit diagram




LIT 1X2-24 - Surge protection device

2804610

<https://www.phoenixcontact.com/us/products/2804610>



Application drawing



LIT 1X2-24 - Surge protection device



2804610

<https://www.phoenixcontact.com/us/products/2804610>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2804610>



EAC

Approval ID: EAC-Zulassung



DNV GL

Approval ID: TAE00001N8



EAC

Approval ID: RU C-DE.*09.B.00169



UL Listed

Approval ID: FILE E 138168

UAE-RoHS

Approval ID: 23-10-88889



ATEX

Approval ID: KEMA 09ATEX0051 X



EAC Ex

Approval ID: RU C-DE.**87.B.00420



IECEx

Approval ID: IECEx KEM 09.0018X



CCC

Approval ID: 2020322316000816



NEPSI-EX

Approval ID: GYJ20.1176X



CCC

Approval ID: 2020322316000816

LIT 1X2-24 - Surge protection device

2804610

<https://www.phoenixcontact.com/us/products/2804610>



UKCA-EX

Approval ID: DEKRA 21UKEX0233 X

LIT 1X2-24 - Surge protection device



2804610

<https://www.phoenixcontact.com/us/products/2804610>

Classifications

ECLASS

ECLASS-11.0	27130807
ECLASS-13.0	27171501

ETIM

ETIM 9.0	EC001625
----------	----------

UNSPSC

UNSPSC 21.0	39121620
-------------	----------

LIT 1X2-24 - Surge protection device



2804610

<https://www.phoenixcontact.com/us/products/2804610>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	7(a), 7(c)-I

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	6159ad9d-3e85-4844-87e7-af02ce7a5544

LIT 1X2-24 - Surge protection device



2804610

<https://www.phoenixcontact.com/us/products/2804610>

Accessories

UC-TM 6 - Marker for terminal blocks

0818085

<https://www.phoenixcontact.com/us/products/0818085>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 80

UC-TM 6 OG - Marker for terminal blocks

0818328

<https://www.phoenixcontact.com/us/products/0818328>



Marker for terminal blocks, Sheet, orange, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 80

LIT 1X2-24 - Surge protection device



2804610

<https://www.phoenixcontact.com/us/products/2804610>

UC-TM 6 YE - Marker for terminal blocks

0818331

<https://www.phoenixcontact.com/us/products/0818331>



Marker for terminal blocks, Sheet, yellow, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 80

UC-TM 6 BU - Marker for terminal blocks

0818344

<https://www.phoenixcontact.com/us/products/0818344>



Marker for terminal blocks, Sheet, blue, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 80

LIT 1X2-24 - Surge protection device

2804610

<https://www.phoenixcontact.com/us/products/2804610>



UC-TM 6 RD - Marker for terminal blocks

0818357

<https://www.phoenixcontact.com/us/products/0818357>



Marker for terminal blocks, Sheet, red, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 80

UC-TM 6 GN - Marker for terminal blocks

0818360

<https://www.phoenixcontact.com/us/products/0818360>



Marker for terminal blocks, Sheet, green, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 80

LIT 1X2-24 - Surge protection device

2804610

<https://www.phoenixcontact.com/us/products/2804610>



SZS 0,6X3,5 VDE - Screwdriver

1212602

<https://www.phoenixcontact.com/us/products/1212602>



Screwdriver, slot-headed, VDE insulated, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com